
STGW12NB60HD

N-CHANNEL 12A - 600V TO-247
PowerMESH™ IGBT

PRELIMINARY DATA

TYPE	V_{CES}	$V_{CE(sat)}$	I_C
STGW12NB60HD	600 V	< 2.8 V	30 A

- HIGH INPUT IMPEDANCE (VOLTAGE DRIVEN)
- LOW ON-VOLTAGE DROP (V_{CESAT})
- LOW GATE CHARGE
- HIGH CURRENT CAPABILITY
- VERY HIGH FREQUENCY OPERATION
- OFF LOSSES INCLUDE TAIL CURRENT
- CO-PACKAGED WITH TURBOSWITCH™ ANTIPARALLEL DIODE




TO-247

DESCRIPTION

Using the latest high voltage technology based on a patented strip layout, STMicroelectronics has designed an advanced family of IGBTs, the PowerMESH™ IGBTs, with outstanding perfomances. The suffix "H" identifies a family optimized to achieve very low switching times for high frequency applications (<120kHz).

INTERNAL SCHEMATIC DIAGRAM



APPLICATIONS

- HIGH FREQUENCY MOTOR CONTROLS
- SMPS AND PFC IN BOTH HARD SWITCH AND RESONANT TOPOLOGIES
- UPS

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CES}	Collector-Emitter Voltage (V_{GS} = 0)	600	V
V_{GE}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current (continuous) at T_c = 25 °C	24	A
I_C	Collector Current (continuous) at T_c = 100 °C	12	A
I_{CM}(•)	Collector Current (pulsed)	96	A
P_{tot}	Total Dissipation at T_c = 25 °C	120	W
	Derating Factor	0.96	W/°C
T_{stg}	Storage Temperature	-65 to 150	°C
T_j	Max. Operating Junction Temperature	150	°C

(•) Pulse width limited by safe operating area

THERMAL DATA

$R_{thj\text{-}case}$	Thermal Resistance Junction-case	Max	1.04	°C/W
$R_{thj\text{-}amb}$	Thermal Resistance Junction-ambient	Max	30	oC/W
$R_{thc\text{-}h}$	Thermal Resistance Case-heatsink	Typ	0.1	°C/W

ELECTRICAL CHARACTERISTICS (T_j = 25 °C unless otherwise specified)

OFF

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{BR(CES)}$	Collector-Emitter Breakdown Voltage	I_C = 250 µA V_{GE} = 0	600			V
I_{CES}	Collector cut-off (V_{GE} = 0)	V_{CE} = Max Rating T_j = 25 °C V_{CE} = Max Rating T_j = 125 °C			250 2000	µA µA
I_{GES}	Gate-Emitter Leakage Current (V_{CE} = 0)	V_{GE} = ± 20 V V_{CE} = 0			± 100	nA

ON (*)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{GE(th)}$	Gate Threshold Voltage	V_{CE} = V_{GE} I_C = 250 µA	3		5	V
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage	V_{GE} = 15 V I_C = 12 A V_{GE} = 15 V I_C = 12 A T_j = 125 °C		2 1.7	2.8	V V

DYNAMIC

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
g_{fs}	Forward Transconductance	V_{CE} =25 V I_C = 12 A		9.5		S
C_{ies} C_{oes} C_{res}	Input Capacitance Output Capacitance Reverse Transfer Capacitance	V_{CE} = 25 V f = 1 MHz V_{GE} = 0		920 120 27		pF pF pF
Q_G Q_{GE} Q_{GC}	Total Gate Charge Gate-Emitter Charge Gate-Collector Charge	V_{CE} = 480 V I_C = 12 A V_{GE} = 15 V		68 10 30		nC nC nC
I_{CL}	Latching Current	V_{clamp} =480 V R_G=10Ω T_j = 150 °C	48			A

SWITCHING ON

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$ t_r	Delay Time Rise Time	V_{CC} = 480 V I_C = 12 A V_{GE}= 15 V R_G = 10Ω		5 46		ns ns
$(di/dt)_{on}$	Turn-on Current Slope	V_{CC} = 480 V I_C = 12 A R_G = 10 Ω V_{GE} = 15 V		800		A/µs
E_{on}(ↄ)	Turn-on Switching Losses	T_j = 125 °C		290		µJ

ELECTRICAL CHARACTERISTICS (continued)

SWITCHING OFF


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
t_c	Cross-Over Time	V_{CC} = 480 V, I_C = 12 A		150		ns
$t_r(v_{off})$	Off Voltage Rise Time	R_{GE} = 10 Ω, V_{GE} = 15 V		27		ns
$t_{d(off)}$	Delay Time			76		ns
t_f	Fall Time			92		ns
E_{off}(**)	Turn-off Switching Loss			0.21		mJ
E_{ts}(○)	Total Switching Loss			0.49		mJ
t_c	Cross-Over Time	V_{CC} = 480 V, I_C = 12 A		229		ns
$t_r(v_{off})$	Off Voltage Rise Time	R_{GE} = 10 Ω, V_{GE} = 15 V		76		ns
$t_{d(off)}$	Delay Time	T_j = 125 °C		95		ns
t_f	Fall Time			200		ns
E_{off}(**)	Turn-off Switching Loss			0.45		mJ
E_{ts}(○)	Total Switching Loss			0.74		mJ

COLLECTOR-EMITTER DIODE


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_f	Forward Current				12	A
I_{fm}	Forward Current pulsed				96	A
V_f	Forward On-Voltage	I_f = 12 A		1.55	2.0	V
		I_f = 12 A, T_j = 125 °C		1.3		V
t_{rr}	Reverse Recovery Time	I_f = 12 A, V_{clamp}= 200 V		100		nS
Q_{rr}	Reverse Recovery Charge	di/dt = 100 A/µS, T_j = 125 °C		330		nC
I_{rrm}	Reverse Recovery Current			6.3		A

(•) Pulse width limited by max. junction temperature
(○) Include recovery losses on the STTA1206 freewheeling diode
(∗) Pulsed: Pulse duration = 300 µs, duty cycle 1.5 %
(**)Losses Include Also The Tail (Jedec Standardization)


Thermal Impedance




Output Characteristics




Transfer Characteristics




Transconductance




Collector-Emitter On Voltage vs Temperature




Collector-Emitter On Voltage vs Collector Current




Gate Threshold vs Temperature




Normalized Breakdown Voltage vs Temperature




Capacitance Variations




Gate Charge vs Gate-Emitter Voltage




Total Switching Losses vs Gate Resistance



Total Switching Losses vs Temperature



Total Switching Losses vs Collector Current



Switching Off Safe Operating Area




Fig. 1: Gate Charge test Circuit

Diode Forward Voltage





Fig. 2: Test Circuit For Inductive Load Switching








Fig. 3: Switching Waveforms



TO-247 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	4.7		5.3	0.185		0.209
D	2.2		2.6	0.087		0.102
E	0.4		0.8	0.016		0.031
F	1		1.4	0.039		0.055
F3	2		2.4	0.079		0.094
F4	3		3.4	0.118		0.134
G		10.9			0.429	
H	15.3		15.9	0.602		0.626
L	19.7		20.3	0.776		0.779
L3	14.2		14.8	0.559		0.582
L4		34.6			1.362	
L5		5.5			0.217	
M	2		3	0.079		0.118



P025P

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 1999 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

http://www.st.com