

Thyristor Surge Suppressors (TSS)

P0080LC - P5000LC Series - DO-27 @10/700μS, 6KV

Description

P0080LC - P5000LC Series are designed to protect broadband equipment such as modems, line card, CPE and DSL from damaging over-voltage transients.


The series provides a surface mount solution that enables equipment to comply with global regulatory standards.

Features and Benefits


- u Low voltage overshoot
- u Low on-state voltage
- u Does not degrade surge capability after multiple surge events within limit
- u Fails short circuit when surged in excess of ratings
- u Low Capacitance

Applicable Global Standards

- u TIA-968-A TIA-968-B
- u ITU K.20/21 Enhanced level
- u ITU K.20/21 Basic Level
- u GR 1089 Inter building
- u GR 1089 Inter building
- u IEC 6100-4-5
- u YD/T 1082
- u YD/T 993
- u YD/T 950




Schematic Symbol



Electrical Parameters

Parameter	Definition
I_S	Switching Current - maximum current required to switch to on state
I_{DRM}	Leakage Current - maximum peak off-state current measured at V_{DRM}
I_H	Holding Current - minimum current required to maintain on state
I_T	On-state Current - maximum rated continuous on-state current
V_S	Switching Voltage - maximum voltage prior to switching to on stat
V_{DRM}	Peak Off-state Voltage - maximum voltage that can be applied while maintaining off state
V_T	On-state Voltage - maximum voltage measured at rated on-state current
C_0	Off-state Capacitance - typical capacitance measured in off state



Thyristor Surge Suppressors (TSS)

P0080LC - P5000LC Series - DO-27 @10/700μS, 6KV

Electrical Characteristics

Part Number	Marking	V_{DRM} @ $I_{DRM}=5\mu A$	V_S @100V/μS	V_T @ $I_T=2.2A$	I_S	I_T	I_H	C_0 @1MHz	
		V min	V max	V max	mA max	A max	mA min	pF min	pF max
P0080LC	P008LC	6	25	4	800	2.2	50	25	150
P0300LC	P03LC	25	40	4	800	2.2	50	15	140
P0640LC	P06LC	58	77	4	800	2.2	150	40	60
P0720LC	P07LC	65	88	4	800	2.2	150	35	60
P0900LC	P09LC	75	98	4	800	2.2	150	25	55
P1100LC	P11LC	90	130	4	800	2.2	150	30	50
P1300LC	P13LC	120	160	4	800	2.2	150	25	45
P1500LC	P15LC	140	180	4	800	2.2	150	25	40
P1800LC	P18LC	170	220	4	800	2.2	150	25	35
P2000LC	P20LC	180	220	4	800	2.2	150	20	35
P2300LC	P23LC	190	260	4	800	2.2	150	25	35
P2600LC	P26LC	220	300	4	800	2.2	150	20	35
P3100LC	P31LC	275	350	4	800	2.2	150	20	35
P3500LC	P35LC	320	400	4	800	2.2	150	20	35
P4000LC	P40LC	360	460	4	800	2.2	150	20	35
P4500LC	P45LC	400	540	4	800	2.2	150	20	35
P5000LC	P50LC	440	600	4	800	2.2	150	20	35

Notes:

- Absolute maximum ratings measured at $T_A = 25^\circ C$ (unless otherwise noted).
- Devices are bi-directional.


Surge Ratings

Series	$2/10\mu S^1$	$8/20\mu S^1$	$10/160\mu S^1$	$10/560\mu S^1$	$10/1000\mu S^1$	$5/310\mu S^1$	I_{TSM} 50/60 Hz	di/dt
	$2/10\mu S^2$	$1.2/50\mu S^2$	$10/160\mu S^2$	$10/560\mu S^2$	$10/1000\mu S^2$	$10/700\mu S^2$		
	A min	A min	A min	A min	A min	A min	A min	Amps/μs max
C	500	400	200	150	100	150	50	500

Notes:

- Current waveform in μs
 - Voltage waveform in μs
- Peak pulse current rating (I_{PP}) is repetitive and guaranteed for the life of the product.
 - I_{PP} ratings applicable over temperature range of $-40^\circ C$ to $+85^\circ C$
 - The device must initially be in thermal equilibrium with $-40^\circ C < T_J < +150^\circ C$

Thermal Considerations

Package	Symbol	Parameter	Value	Unit
DO-27 	T_J	Operating Junction Temperature Range	- 40 to + 150	$^\circ C$
	T_S	Storage Temperature Range	- 40 to +150	$^\circ C$
	$R_{\theta JA}$	Thermal Resistance: Junction to Ambient	90	$^\circ C/W$



Thyristor Surge Suppressors (TSS)

P0080LC - P5000LC Series - DO-27 @10/700μS, 6KV

Characteristic Curves

Figure 1 - V-I Characteristics




Figure 2 - $t_r \times t_d$ Pulse Waveform




Figure 3 - Normalized V_S Change Versus Junction Temperature





Figure 4 - Normalized DC Holding Current Versus Case Temperature



Thyristor Surge Suppressors (TSS)

P0080LC - P5000LC Series - DO-27 @10/700μS, 6KV


Environmental Specifications

High Temp Voltage Blocking	80% Rated VDRM (VAC Peak) +125°C or +150°C, Lead Material Copper Alloy High Temp Voltage Blocking 504 or 1008 hrs. MIL-STD-750 (Method 1040) JEDEC, JESD22-A-101
Temp Cycling	-65°C to +150°C, 15 min. dwell, 10 up to 100 cycles. MIL-STD-750 (Method 1051) EIA/JEDEC, JESD22-A104
Biased Temp & Humidity	52 VDC (+85°C) 85%RH, 504 up to 1008 hrs. EIA/JEDEC, JESD22-A-101
High Temp Storage	+150°C 1008 hrs. MIL-STD-750 (Method 1031) JEDEC, JESD22-A-101
Low Temp Storage	-65°C, 1008 hrs.
Thermal Shock	0°C to +100°C, 5 min. dwell, 10 sec. transfer, Thermal Shock 10 cycles. MIL-STD-750 (Method 1056) JEDEC, JESD22-A-106
Autoclave (Pressure Cooker Test)	+121°C, 100%RH, 2atm, 24 up to 168 hrs. EIA/Cooker Test) JEDEC, JESD22-A-102
Resistance to Solder Heat	+260°C, 30 secs. MIL-STD-750 (Method 2031
Moisture Sensitivity Level	85%RH, +85°C, 168 hrs., 3 reflow cycles Level (+260°C Peak). JEDEC-J-STD-020, Level 1

Physical Specifications

Lead Material	Copper Alloy
Terminal Finish	100% Matte-Tin Plated
Body Material	UL recognized epoxy meeting flammability classification 94V-0

Soldering Parameters




Reflow Condition		Lead-free assembly
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150°C
	-Temperature Max ($T_{s(max)}$)	+200°C
	-Time (min to max) (t_s)	60 -180 Seconds
Average ramp up rate (Liquidus Temp T_L to peak		3°C/Second Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/Second Max
Reflow	- Temperature (T_L) (Liquidus)	+217°C
	- Time (min to max) (t_s)	60 -150 Seconds
Peak Temperature (T_P)		260 +0/-5°C
Time within 5°C of actual peak Temperature (t_p)		30 Seconds Max
Ramp-down Rate		6°C/Second Max
Time 25°C to peak Temperature (T_P)		8 minutes Max
Do not exceed		+260°C


Thyristor Surge Suppressors (TSS)

P0080LC - P5000LC Series - DO-27 @10/700μS, 6KV


Part Numbering



Part Marking



Dimensions DO-27




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
B	0.028	0.042	0.711	1.067
D	0.190	0.205	4.826	5.207
G	0.360	0.375	9.146	9.527
L	1.000		25.40	

Packaging

Part Number	Description	Quantity	Industry Standard
Pxxx0LC	DO-27 Axial Tape & Reel	1000	EIA-RS-296-D
	DO-27 Bulk Pack	500	N/A

Tape and Reel Specifications DO-27



Dimensions
are in inches
(and millimeters)

