

Product Information

HES26MC-2G Series

24+2G-Port Rackmount Gigabit Managed Ethernet Switches



Features

- ❖ RingOn (recovery time < 15ms), RSTP for Network Redundancy
- ❖ Manage network operation, configuration, and security via web browser
- ❖ VLAN broadcast domain configuration
- ❖ -40 to +75°C Operating Temperature Range (W models)



Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

The HES26MC-2G series industrial managed rackmount switches are designed to seamlessly integrate your control networks and field networks. The switches can operate in extreme operating temperatures ranging from -40 to +75°C, and are equipped with up to two AC power inputs for conventional usage as well as for advanced Ethernet switching functionality to ensure the reliability of your communication network. The HES26MC-2G switches are designed to meet the rigorous demands of mission critical applications, including traffic control systems, networks along railway tracks, maritime applications, mining and oil/gas industry applications.

Specifications

Technology	
Standard :	IEEE802.3, 802.3u, 802.3x, 802.3ab, 802.1Q, 802.1p
Processing Type :	Store and forward
Broadcast Storm :	Automatic Broadcast Storm Control
Management :	by Web Browser
RingOn :	Recovery Time within 15ms
Flow Control :	Full Duplex Flow Control, Half Duplex Back Pressure Control
Protocols :	IGMP Snooping, GMRP, SNMPv1/v2c/v3, DHCP Client, HTTP, HTTPS, Telnet, NTP Client
Switch Properties	
MAC Table Size :	8K
Priority Queues :	4
Max. Number VLANs :	64
VLAN ID Range :	VID 1 to 4094
IGMP Groups :	256
Interface	
RJ45 Port :	10/100BaseT(X) or 10/100/1000BaseT(X) auto negotiation speed
Fiber Ports :	100BaseFX ports (SC/ST connector)
Fiber Module :	1000Base-LX (2 SFP slots)
LED Indicators :	Power, Port Status, 10/100/1000M
Console port :	DB9 male
Output Warning :	Relay, Standard 2 Pin
Power Requirements	
Input Voltage :	120~370VDC @ 30W MAX 85~265VAC @ 30VA MAX
Input Connection :	Barrier type terminal blocks
Physical Characteristics	
Case :	Slim Metal Case, IP30 Design
Dimensions :	443×44×260mm
Installation :	DIN Rail or Panel Mounting

Optical Fiber			
Mode	Multi-mode	Single Mode	Single Mode
Transmission Distance	2km	20km	20km
Centre Wavelength	1310nm	1310nm	1310nm
Cable Size	62.5/125um	9/125um	9/125um
TX Power(dBm)	-20~-10dBm	-15~-8dBm	-8~-2dBm
RX Power(dBm)	< -32dBm	< -32dBm	< -24dBm
Transmission Rate	100Mbps	100Mbps	1000Mbps
Environment Limits			
Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C		
Storage Temp. :	-40 to 85°C		
Ambient Relative Humidity :	5 to 95%(Non-condensing)		
Standards and Certifications			
EMI :	FCC Part15, CISPR(EN55022) Class A EN61000-4-2(ESD) Level 3, EN61000-4-3(RS) Level 3, EN61000-4-4(EFT) Level 3, EN61000-4-5(Surge) Level 3, EN61000-4-6(CS) Level 3, EN61000-6-2		
EMS :			
Shock :	IEC 60068-2-27		
Freefall :	IEC 60068-2-32		
Vibration :	IEC 60068-2-6		
Warranty			
Warranty Period :	3 years		

Ordering Information

HES26MC-2G Series

HES26MC-2G-VH	Rackmount Managed, 24 x 100Mbps Copper Port, 2 x Gigabit combo Interface, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-VHW	Rackmount Managed, 24 x 100Mbps Copper Port, 2 x Gigabit combo Interface, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-2SC-VH	Rackmount Managed, 22 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 2km, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-2SC-VHW	Rackmount Managed, 22 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 2km, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-2SSC-VH	Rackmount Managed, 22 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 20km, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-2SSC-VHW	Rackmount Managed, 22 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 20km, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-4SC-VH	Rackmount Managed, 20 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 2km, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-4SC-VHW	Rackmount Managed, 20 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 2km, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-4SSC-VH	Rackmount Managed, 20 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 20km, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2G-4SSC-VHW	Rackmount Managed, 20 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC Connectors, 2 x Gigabit Combo Port, 20km, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector