


InGaAs PIN photodiodes



G8941 series

Sub-mount type photodiodes for LD monitor

Features

- Photosensitive area
G8941-01: $\phi 1$ mm
G8941-02: $\phi 0.5$ mm
G8941-03: $\phi 0.3$ mm
- Miniature package: $2 \times 2 \times 1$ mm
- Precise chip position tolerance: ± 0.075 mm

Applications

- LD monitor

Structure

Parameter	G8941-01	G8941-02	G8941-03	Unit
Photosensitive area	$\phi 1$	$\phi 0.5$	$\phi 0.3$	mm

Absolute maximum ratings

Parameter	Symbol	Remark	G8941-01	G8941-02	G8941-03	Unit
Reverse voltage	V_R Max.		10	20	20	V
Operating temperature	T_{opr}	*	-40 to +85			$^{\circ}\text{C}$
Storage temperature	T_{stg}		-55 to +125			$^{\circ}\text{C}$

* In N₂ environment or in vacuum


Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

Electrical and optical characteristics (Ta=25 °C)

Parameter	Symbol	Condition	G8941-01			G8941-02			G8941-03			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Spectral response range	λ		0.9 to 1.7			0.9 to 1.7			0.9 to 1.7			μm
Photosensitivity	S	$\lambda=1.31 \mu\text{m}$	0.8	0.9	-	0.8	0.9	-	0.8	0.9	-	A/W
		$\lambda=1.55 \mu\text{m}$	0.85	0.95	-	0.85	0.95	-	0.85	0.95	-	
Dark current	I_D	$V_R=5 \text{ V}$	-	1	5	-	0.5	2.5	-	0.3	1.5	nA
Shunt resistance	Rsh	$V_R=10 \text{ mV}$	-	100	-	-	300	-	-	1000	-	M Ω
Terminal capacitance	Ct	$V_R=5 \text{ V}$ $f=1 \text{ MHz}$	-	90	-	-	12	-	-	5	-	pF
Cutoff frequency	f_c	$V_R=5 \text{ V}$ $R_L=50 \Omega$	-	35	-	-	200	-	-	400	-	MHz
Noise equivalent power	NEP	$\lambda=\lambda_p$	2×10^{-14}			8×10^{-15}			4×10^{-15}			W/Hz ^{1/2}
Detectivity	D*	$\lambda=\lambda_p$	5×10^{12}			5×10^{12}			5×10^{12}			cm ² Hz ^{1/2} /W


The G8941 series may be damaged by electrostatic discharge, etc. Be careful when using the G8941 series.

Spectral response




KIRDB0002EB

Dark current vs. reverse voltage




KIRDB00270EB

Terminal capacitance vs. reverse voltage



KIRDB0271EA


Dark current vs. temperature



KIRDB0272EA


Dimensional outlines (unit: mm)

G8941-01




KIRDA0159EB

G8941-02



KIRDA0160EB

G8941-03



KIRDA0161EB

Related information

www.hamamatsu.com/sp/ssd/doc_en.html

Precautions

- Disclaimer
- Surface mount type products

Information described in this material is current as of July, 2015.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

HAMAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, N.J. 08807, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39) 02-93581733, Fax: (39) 02-93581741

China: Hamamatsu Photonics (China) Co., Ltd.: B1201, Jiaming Center, No.27 Dongsanhuan Beilu, Chaoyang District, Beijing 100020, China, Telephone: (86) 10-6586-6006, Fax: (86) 10-6586-2866