



- Headers (350 & 450) use MM# 3404 pins. See page 179 for details.
- Sockets (310 & 410) use MM# 1005 receptacles and accept pin diameters from .015-.025. See page 137 for details.
- Coplanarity .005" (Single Row max 10 pins; Double Row max 20 pins). For higher pin counts contact technical support.
- Insulators are high temp. thermoplastic.



For RoHS compliance select ◇ plating code.

Ordering Information

Fig. 1L	Single Row Header, Left Hand Footprint Odd or Even # of pins	350-XX-1_ _-00-106000	
	Specify # of pins	02-64	
Fig. 1R	Single Row Header, Right Hand Footprint Even # of pins	350-XX-1_ _-00-107000	
	Specify even # of pins	02-64	
Fig. 2	Double Row Header, Even # of pins	450-XX-2_ _-00-106000	
	Specify even # of pins	04-72	
SPECIFY PLATING CODE XX=		10◇	90
Pin Plating		10μ" Au	200μ" Sn/Pb
Fig. 3L	Single Row Socket, Left Hand Footprint Odd or Even # of pins	310-43-1_ _-41-105000	
	Specify # of pins	02-64	
Fig. 3R	Single Row Socket, Right Hand Footprint Even # of pins	310-43-1_ _-41-107000	
	Specify even # of pins	02-64	
Fig. 4	Double Row Socket, Even # of pins	410-43-2_ _-41-105000	
	Specify even # of pins	04-72	
PLATING CODE =		43◇	
Sleeve (Pin)			200μ" Sn
Contact (Clip)			30μ" Au