



SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE 50 Volts CURRENT 30 Amperes

FEATURES

- * Low switching noise
- * Low forward voltage drop
- * Low thermal resistance
- * High current capability
- * High switching capability
- * High surge capability
- * High reliability

MECHANICAL DATA


- * Case: D2-PAK molded plastic
- * Epoxy: Device has UL flammability classification 94V-O
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 3.61 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
resistive or inductive load.



D2-PAK



MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	SR3050CS	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	Volts
Maximum RMS Voltage	V_{RMS}	35	Volts
Maximum DC Blocking Voltage	V_{DC}	50	Volts
Maximum Average Forward Rectified Current at Derating Case Temperature	I_O	30	Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	300	Amps
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	1.5	°C/W
	$R_{\theta JA}$	30	°C/W
Operating Temperature Range	T_J	175($T_J \leq 200^\circ\text{C}$ in By pass Mode)	°C
Storage Temperature Range	T_{STG}	-55 to + 175	°C

ELECTRICAL CHARACTERISTICS(@TA=25 °C unless otherwise noted)

CHARACTERISTICS	SYMBOL	SR3050CS	UNITS
Maximum Instantaneous Forward Voltage at 15.0A DC	V_F	.65	Volts
Maximum Average Reverse Current @ $T_A = 25^\circ\text{C}$	I_R	1.0	mA
at Rated DC Blocking Voltage @ $T_A = 100^\circ\text{C}$		10	mA

- NOTES : 1. Thermal Resistance : Heat-sink mounted.
2. Suffix "A" = Common Anode.
3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".
4. Available in Halogen-free epoxy by adding suffix -HF after the part nbr.

2010-04
REV:O

RATING AND CHARACTERISTICS CURVES (SR3050CS)




FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL REVERSE CHARACTERISTICS




FIG.3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.