



**APPLIED  
CONCEPTS INC.**

397 Route 281 - P.O. BOX 453  
Tully, New York 13159-0453  
Phone: (315) 696-6676 Fax: (315) 696-9923  
www.acipower.com

**AC7-28-1175**

**CCFL INVERTER**

*(For Dual Tube Applications)*

**PRODUCT DATA SHEET**

10/10/00

The AC7-28-1175 is designed to drive 2 CCFLs to a nominal current level of 7.0mA.

Intensity control (0-100%) is accomplished by the user providing a variable dc level of 0V(off) to 5V(full-on) at pin 3 of CON1.

A +5V level is available at pin 4 of CON1 for powering the high-side of the intensity control potentiometer.

The lamp outputs are open and short circuit protected.

**Specifications:**

- Vin = +28V +/- 10%
- CCFL strike voltage = 1500Vrms @ Vin=28V
- CCFL tube current = 7.0mA/tube @ 100% intensity/Vin=28V
- Recommended CCFL sustaining voltage = 500Vrms - 700Vrms
- Nominal tube current frequency = 57khz +/- 10%
- Nominal pwm frequency = 98Hz +/- 3%
- Pwm duty cycle range = 0 to 100%
- Average electrical efficiency >87%

**Additional control capability:\***

- Enable/Disable function
- Simple 1 or 2 button intensity control
- CDS ambient light sensor control
- Synchronization to display frame-rate capable
- Two-wire(variable resistance) intensity control
- Serial communication control

\* Please contact factory for information

