

SBC



ISA-588LF

ISA Intel® Atom™ N270
CPU Card w/VGA /
Audio / LAN

Features :

- Intel® Atom™ N270 (1.6GHz) CPU on board
- Intel® 945GSE + ICH7M+ FWH (FSB : 533MHz)
- 1 x 200-Pin DDR2 SO-DIMM, supports DDR2 400/533 up to 2GB
- Expansion slot for one PC/104
- Fanless Solution



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714- 996-7200 FAX: +1-714- 996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.


OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>



ISO CERTIFIED
9001 14001

ISA-588LF

ISA Intel® Atom™ N270 CPU Card w/VGA / Audio / LAN



Specifications	
System	
CPU Support	Intel® Atom™ N270 (1.6GHz) CPU on board
CPU Frequency	1.6GHz
Chipset	Intel® 945GSE + ICH7M (FSB: 533MHz)
DRAM	1 x 200-Pin DDR2 SO-DIMM, supports DDR2 400/533 up to 2GB
BIOS	Phoenix-Award PnP BIOS Memory size 8 Mbit
Watchdog	1~255 secs Watchdog timer selectable w / Reset / NMI
Power Supply	Support AT / ATX power
Power Requirement	+5V, +12V
Power Consumption	+5V: 5.4A/ +12V: 1A
Dimension	185 mm x 122 mm (7.28" x 4.8")
Certificate	FCC / CE

I/O Chipset	
SATA Interface	2 x S-ATA II connector
IDE Interface	1 x IDE connector with 44-pin pin-header on board
SSD	1 x Compact flash slot (IDE)
FDD Interface	1 x FDD connector with 34-pin box-header
Expansion BUS	1 x PC/104
Serial Port	2 ports, 16550 UARTs RS-232 COM 1 for RS-232; COM 2 for RS-232/422/485
Parallel Port	1 x Parallel port (SPP / EPP / ECP)
IrDA	1 (SIR)
Keyboard	1 x Mini DIN connector

Mouse	1 x Mini DIN connector
LAN	Single port Intel® 82583V GbE support wake-on-LAN with ATX power
Audio	Support HD audio daughter board
D/I/O	HD audio, Realtek ALC262
USB	4 x USB 2.0

Display	
Graphics	Build-in Intel® 945GSE Supports CRT, LVDS
LCD Interface	18/36 bit LVDS

Environment	
Operation Temp.	0° ~ 60° C (32° ~ 140° F)
Storage Temp.	- 40° ~ 85° C (- 40° ~ 185° F)
Humidity	Operation humidity 20 ~ 90%, storage humidity 20 ~ 95%

Ordering Information	
ISA-588LF	Half-size ISA CPU card w/ Intel® Atom™ N270 CPU VGA / LDVS / Audio/ LAN (GbE) / 2 x COM

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Sep. 2011.