

MARKING / Aufdruck


MEDER 5-C YM

MEDER-Label, Type,
 Production code EN60062
 MEDER-Logo, Typ,
 Produktionscode EN60062

angular variation of the pins
 up to 7.5° possible
 Winkelabweichung der Anschlussbeine
 bis zu 7.5° möglich

CIRCUIT DIAGRAM

Schaltbild



Abmessungen / dimensions (mm)
 unspecified tolerances acc. to DIN ISO 2768-m

| Magnetic properties | Conditions | Min | Typ | Max | Unit |
|---------------------|------------|--------|-----|------|------|
| Pull-In | at 20 °C | 10,8 | | 18,3 | VDC |
| Test equipment | | KMS-16 | | | |

| Special Product Data | Conditions | Min | Typ | Max | Unit |
|----------------------|--|----------------------------|-----|-----|------|
| Contact - form | | A - NO | | | |
| Contact rating | Any DC combination of V & A not to exceed their individual max.'s | | | 10 | W |
| Switching voltage | DC or Peak AC | | | 180 | VDC |
| Carry current | DC or Peak AC | | | 0,5 | A |
| Switching current | DC or Peak AC | | | 0,5 | A |
| Sensor-resistance | measured with 40% overdrive | | | 150 | mOhm |
| Housing material | | PBT glass fibre reinforced | | | |
| Case color | | blue | | | |
| Sealing compound | | Epoxy resin | | | |

| Environmental data | Conditions | Min | Typ | Max | Unit |
|---------------------|-----------------------------|--------------|-----|-----|------|
| Shock | 1/2 sine wave duration 11ms | | | 30 | g |
| Vibration | from 10 - 2000 Hz | | | 20 | g |
| Ambient temperature | | -20 | | 85 | °C |
| Storage temperature | | -35 | | 85 | °C |
| Cleaning | | fully sealed | | | |