

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0901301334

Status:

Active

Overview:

cgrid_iii

Description:

2.54mm (.100") Pitch C-Grid III™ Header, Dual Row, Vertical, Shrouded, Fully Loaded, 34 Circuits, Black, 0.76µm (30µ") Gold (Au) Selective Plating


Documents:

3D Model

RoHS Certificate of Compliance (PDF)

Drawing (PDF)

General	
Product Family	PCB Headers
Series	90130
Application	Wire-to-Board
Overview	cgrid_iii
Product Name	C-Grid III™
Physical	
Breakaway	No
Circuits (Loaded)	34
Circuits (maximum)	34
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.114 In
PC Tail Length (mm)	2.90 mm
PCB Locator	No
PCB Retention	None
PCB Thickness Recommended (in)	0.063 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Plating min: Mating (µin)	30.48
Plating min: Mating (µm)	0.762
Plating min: Termination (µin)	120
Plating min: Termination (µm)	3
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Closed Ends
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +125°C
Termination Interface: Style	Through Hole



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

90130Series

Mates With

90142 C-Grid III™ Crimp Housing

Electrical

Current - Maximum per Contact	3A
Voltage - Maximum	350V AC/DC

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260

Material Info




Reference - Drawing Numbers

Packaging Specification	PK-90130-001, PK-91814-005
Sales Drawing	SDA-90130

This document was generated on 05/26/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

VERSION FULLY LOADED



NOTES

1.MATERIAL:-


- PIN:- (0.635)/.025 SQ. BRASS WIRE.
- HOUSING:- 15% GLASS FILLED POLYESTER
- UL 94 V-0 COLOUR BLACK

2.FOR PLATING VERSIONS AND VOID VERSIONS SEE SHEET 2.

3.MEASUREMENT POINT FOR MINIMUM PLATING THICKNESS.

4.FOR PRODUCT SPEC SEE PS-99020-0001

5.RECOMMENDED PCB THICKNESS: 1.6mm



No. OF CKTS	DIM A	DIM B	DIM C
6	(5.08) / .200	(9.96) / .392	(8.12) / .320
8	(7.62) / .300	(12.50) / .492	(10.66) / .420
10	(10.16) / .400	(15.04) / .592	(13.20) / .520
12	(12.70) / .500	(17.58) / .692	(15.74) / .620
14	(15.24) / .600	(20.12) / .792	(18.28) / .720
16	(17.78) / .700	(22.66) / .892	(20.82) / .820
18	(20.32) / .800	(25.20) / .992	(23.36) / .920
20	(22.86) / .900	(27.74) / 1.092	(25.90) / 1.020
22	(25.40) / 1.000	(30.28) / 1.192	(28.44) / 1.120
24	(27.94) / 1.100	(32.82) / 1.292	(30.98) / 1.220
26	(30.48) / 1.200	(35.36) / 1.392	(33.52) / 1.320
28	(33.02) / 1.300	(37.90) / 1.492	(36.06) / 1.420
30	(35.56) / 1.400	(40.44) / 1.592	(38.60) / 1.520
32	(38.10) / 1.500	(42.98) / 1.692	(41.15) / 1.620
34	(40.64) / 1.600	(45.52) / 1.792	(43.68) / 1.720
36	(43.18) / 1.700	(48.06) / 1.892	(46.22) / 1.820
38	(45.72) / 1.800	(50.60) / 1.992	(48.76) / 1.920
40	(48.26) / 1.900	(53.14) / 2.092	(51.30) / 2.020
42	(50.80) / 2.000	(55.68) / 2.192	(53.84) / 2.120
44	(53.34) / 2.100	(58.22) / 2.292	(56.38) / 2.220
46	(55.88) / 2.200	(60.76) / 2.392	(58.92) / 2.320
48	(58.42) / 2.300	(63.30) / 2.492	(61.46) / 2.420
50	(60.96) / 2.400	(65.84) / 2.592	(64.00) / 2.520
52	(63.50) / 2.500	(68.38) / 2.692	(66.54) / 2.620
54	(66.04) / 2.600	(70.92) / 2.792	(69.08) / 2.720
56	(68.58) / 2.700	(73.46) / 2.892	(71.62) / 2.820
58	(71.12) / 2.800	(76.00) / 2.992	(74.16) / 2.920
60	(73.66) / 2.900	(78.54) / 3.092	(76.70) / 3.020
62	(76.20) / 3.000	(81.08) / 3.192	(79.24) / 3.120
64	(78.74) / 3.100	(83.62) / 3.292	(81.78) / 3.220
66	(81.28) / 3.200	(86.16) / 3.392	(84.32) / 3.320
68	(83.82) / 3.300	(88.70) / 3.492	(86.86) / 3.420

RE-POSITION DIM B EC NO: S2010-0811 DRWNSKANG CHKD:ATSEE APPR:MLONG B1	2010/03/25	2010/03/31	2010/03/31	QUALITY SYMBOLS <div>F_A=0</div> <div>F_B=0</div> <div>F_C=0</div> <div>DESCRIPTION</div> <div>REV</div>	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION <div>⊙</div> <div>◻</div>	
	mm		INCH		DRAWN BY		DATE		C-GRID III DUAL ROW STRAIGHT SHROUDED HEADER MOLEX INCORPORATED			
	4 PLACES ± --- ± ---		KS		1988/08/23							
	3 PLACES ± --- ± .004		CHECKED BY		DATE							
	2 PLACES ± 0.10 ± ---		ATSEE		2010/02/11							
	1 PLACE ± --- ± ---		APPROVED BY		DATE		MOLEX					
	ANGULAR ±1/2°		MLONG		2010/02/19							
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		DOCUMENT NO.		SDA-90130					
			SEE TABLE		SHEET NO.							
			SIZE		1 OF 4							
A3												
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												

	10	9	8	7	6	5	4	3	2	1							
	NO OF CKTS	HSG CKT SIZE	PART NUMBER			NOTES: 1. FOR ASSY SEE SHEET 1. 2. FOR PLATING DETAILS SEE SDES-99000-0003											
			PLATING TYPE A	PLATING TYPE E	PLATING TYPE F												
F	6	6	90130-X106	90130-X206	90130-X306	90130 - * * * * <div>INDICATES CIRCUIT HOUSING SIZE (EXCEPTION ON VOIDED OPTION - SEE TABLE FOR HOUSING CIRCUIT SIZE)</div> <div>PLATING 1 - TYPE A 2 - TYPE E 3 - TYPE F 4 - TYPE G</div> <div>STYLE: - STRAIGHT ASSY - 1. VERSION FULLY LOADED BLACK 8. VERSION WITH VOIDS</div>											
	8	8	X108	X208	X308												
	10	10	X110	X210	X310												
	12	12	X112	X212	X312												
	14	14	X114	X214	X314												
	16	16	X116	X216	X316												
	18	18	X118	X218	X318												
	20	20	X120	X220	X320												
E	22	22	X122	X222	X322												
	24	24	X124	X224	X324												
	26	26	X126	X226	X326												
	28	28	X128	X228	X328												
D	30	30	X130	X230	X330												
	32	32	X132	X232	X332												
	34	34	X134	X234	X334												
	36	36	X136	X236	X336												
	38	38	X138	X238	X338												
	40	40	X140	X240	X340												
	42	42	X142	X242	X342												
	44	44	X144	X244	X344												
C	46	46	X146	X246	X346												
	48	48	X148	X248	X348												
	50	50	X150	X250	X350												
	52	52	X152	X252	X352												
	54	54	X154	X254	X354												
	56	56	X156	X256	X356												
	58	58	X158	X258	X358												
	60	60	X160	X260	X360												
B	62	62	X162	X262	X362												
	64	64	X164	X264	X364												
	66	66	X166	X266	X366												
	68	68	90130-X168	90130-X268	90130-X368												
	VERSION FULLY LOADED																
A																	

NO OF CKTS	HSG CKT SIZE	VOIDED PART NUMBER	VOID POSITION	PLATING TYPE
11	12	90130-8212	12	E
9	10	90130-8309	2	F
9	10	90130-8311	1	F
11	12	90130-8213	2	E
11	12	90130-8313	2	F

VOIDED OPTION

RE-POSITION DIM B EC NO: S2010-0811 DRWN:SKANG CHKD:ATSEE APPR:MLONG	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		<div><div><div>F</div>=0</div><div><div>F</div>=0</div><div><div>F</div>=0</div></div>	4 PLACES ± --- INCH ± --- 3 PLACES ± --- ± .004 2 PLACES ± 0.10 ± --- 1 PLACE ± --- ± --- ANGULAR ± 1/2°	DRAWN BY KS	DATE 1988/08/23	TITLE C-GRID III DUAL ROW STRAIGHT SHROUDED HEADER MOLEX INCORPORATED	SHEET NO. 2 OF 4			
				CHECKED BY ATSEE	DATE 2010/02/11					
				APPROVED BY MLONG	DATE 2010/02/19					
B1		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		DOCUMENT NO. SDA-90130				
				SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

tb_frame_A3_P_AM_T
Rev. F 2009/06/18

F

E

D

C

B

A

10

9

8

7

6


5

4



3

2

1



VERSION FULLY LOADED

RECOMMENDED P.C. BOARD
HOLE PATTERN

NOTES

1.MATERIAL:-


- PIN:- (0.635)/.025 SQ. BRASS WIRE.
- HOUSING:- 15% GLASS FILLED POLYESTER
- UL 94 V-0 COLOUR BLACK

2.FOR PLATING VERSIONS AND VOID VERSIONS
SEE SHEET 2.

3.MEASUREMENT POINT FOR MINIMUM PLATING THICKNESS.

4.FOR PRODUCT SPEC SEE PS-99020-0001

5.RECOMMENDED PCB THICKNESS: 1.6mm

EXTENT OF
GOLD PLATE

RE-POSITION DIM B		DESCRIPTION	QUALITY SYMBOLS
REV	DATE		
B1	2010/03/25	DRWN:SKANG	FA=0
	2010/03/31	CHKD:ATSEE	FB=0
	2010/03/31	APPR:MLONG	FC=0

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .004
2 PLACES	± 0.10	± ---
1 PLACE	± ---	± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONSDIMENSION STYLE
MM/IN

DRAWN BY	DATE
KS	1988/08/23
CHECKED BY	DATE
ATSEE	2010/02/11
APPROVED BY	DATE
MLONG	2010/02/19

MATERIAL NO.

SEE TABLE

SIZE
A3SCALE
NTS

TITLE

C-GRID III

DUAL ROW STRAIGHT

SHROUDED HEADER

MOLEX INCORPORATED

DOCUMENT NO.

SDA-90130

SHEET NO.

3 OF 4

DESIGN UNITS
METRICTHIRD ANGLE
PROJECTIONTHIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

9

8

7

6

5

4

3

2

1

	10	9	8	7	6	5	4	3	2	1			
	NO OF CKTS	HSG CKT SIZE	PART NUMBER										
			PLATING TYPE A	PLATING TYPE E	PLATING TYPE F								
F	6	6	90130-X106	90130-X206	90130-X306							F	
	8	8	↑ X108	↑ X208	↑ X308								
	10	10	X110	X210	X310								
	12	12	X112	X212	X312								
	14	14	X114	X214	X314								
	16	16	X116	X216	X316								
	18	18	X118	X218	X318								
	20	20	X120	X220	X320								
	E	22	22	X122	X222	X322							E
		24	24	X124	X224	X324							
		26	26	X126	X226	X326							
		28	28	X128	X228	X328							
30		30	X130	X230	X330								
32		32	X132	X232	X332								
	34	34	X134	X234	X334								
	36	36	X136	X236	X336								
	D	38	38	X138	X238	X338							D
		40	40	X140	X240	X340							
		42	42	X142	X242	X342							
		44	44	X144	X244	X344							
46		46	X146	X246	X346								
48		48	X148	X248	X348								
	50	50	X150	X250	X350								
	52	52	X152	X252	X352								
	C	54	54	X154	X254	X354							C
		56	56	X156	X256	X356							
		58	58	X158	X258	X358							
		60	60	X160	X260	X360							
62		62	X162	X262	X362								
64		64	X164	X264	X364								
	66	66	↓ X166	↓ X266	↓ X366								
	68	68	90130-X168	90130-X268	90130-X368							B	
	VERSION FULLY LOADED												
A											A		

NOTES:

1. FOR ASSY SEE SHEET 3.

2. FOR PLATING DETAILS SEE SDES-99000-0003

90130 - * * * *

INDICATES CIRCUIT HOUSING SIZE

PLATING

1 - TYPE A

2 - TYPE E

3 - TYPE F

STYLE:- RIGHT ANGLE ASSY

- 3 VERSION FULLY LOADED BLACK


RE-POSITION DIM B EC NO: S2010-0811 DRWN:SKANG CHKD:ATSEE APPR:MLONG 2010/03/25 2010/03/31 2010/03/31	QUALITY SYMBOLS F=0 F=0 F=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .004 2 PLACES ± 0.10 ± --- 1 PLACE ± --- ± --- ANGULAR ± 1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE MM/IN		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
			DRAWN BY KS	DATE 1988/08/23	C-GRID III DUAL ROW STRAIGHT SHROUDED HEADER MOLEX INCORPORATED			
			CHECKED BY ATSEE	DATE 2010/02/11				
			APPROVED BY MLONG		DATE 2010/02/19	DOCUMENT NO. SDA-90130		SHEET NO. 4 OF 4
B1	REV	SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

tb_frame_A3_P_AM_T
Rev. F 2009/06/18

9867654321

NOTES:

1. FOR ASSY SEE SHEET 3.
2. FOR PLATING DETAILS SEE SDES-99000-0003



NO OF CKTS	HSG CKT SIZE	PART NUMBER		
		PLATING TYPE A	PLATING TYPE E	PLATING TYPE F
6	6	90130-X106	90130-X206	90130-X306
8	8	X108	X208	X308
10	10	X110	X210	X310
12	12	X112	X212	X312
14	14	X114	X214	X314
16	16	X116	X216	X316
18	18	X118	X218	X318
20	20	X120	X220	X320
22	22	X122	X222	X322
24	24	X124	X224	X324
26	26	X126	X226	X326
28	28	X128	X228	X328
30	30	X130	X230	X330
32	32	X132	X232	X332
34	34	X134	X234	X334
36	36	X136	X236	X336
38	38	X138	X238	X338
40	40	X140	X240	X340
42	42	X142	X242	X342
44	44	X144	X244	X344
46	46	X146	X246	X346
48	48	X148	X248	X348
50	50	X150	X250	X350
52	52	X152	X252	X352
54	54	X154	X254	X354
56	56	X156	X256	X356
58	58	X158	X258	X358
60	60	X160	X260	X360
62	62	X162	X262	X362
64	64	X164	X264	X364
66	66	X166	X266	X366
68	68	90130-X168	90130-X268	90130-X368

NO OF CKTS	HSG CKT SIZE	VOIDED PART NUMBER	VOID POSITION	PLATING TYPE
11	12	90130-8212	12	E
9	10	90130-8309	2	F
9	10	90130-8311	1	F
11	12	90130-8213	2	E
11	12	90130-8313	2	F

VOIDED OPTION

NOTES:
1. FOR ASSY SEE SHEET 1.
2. FOR PLATING DETAILS SEE SDES-99000-0003

90130 - * * * *
INDICATES CIRCUIT HOUSING SIZE
(EXCEPTION ON VOIDED OPTION -
SEE TABLE FOR HOUSING CIRCUIT SIZE)
PLATING
1 - TYPE A
2 - TYPE E
3 - TYPE F
4 - TYPE G
STYLE* - STRAIGHT ASSY
- 1. VERSION FULLY LOADED BLACK
8. VERSION WITH VOIDS

VERSION FULLY LOADED

Changed 8212 to void 2
EC NO: E2010-0123
DRWN:BMAGUIRE 2009/10/15
CHKD: 2009/10/15
APPR:BMAGUIRE 2009/10/15

DESCRIPTION
REV

QUALITY SYMBOLS
=0
=0

GENERAL TOLERANCES (UNLESS SPECIFIED)
mm INCH
4 PLACES ± --- ± ---
3 PLACES ± --- ± ---
2 PLACES ± --- ± ---
1 PLACE ± --- ± ---
ANGULAR ± ---°
DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE
MM ONLY

DRAWN BY DATE
KS 1987/09/10

CHECKED BY DATE

APPROVED BY DATE

MATERIAL NO.

SIZE
A2

SCALE
1:1

DESIGN UNITS
METRIC

THIRD ANGLE PROJECTION

TITLE
C-GRID III DUAL ROW
STRAIGHT SHROUDED
HEADER

MOLEX

MOLEX INCORPORATED

MATERIAL NO. SDA-90130
DOCUMENT NO. SHEET NO.
2 OF 4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

1b_frame_A2_P_ME_T
Rev. E 2006/04/15

13121110987654321