STRADA-2X2-ME-WIDE1

Beam with excellent longitudinal luminance uniformity fulfilling EN13201 M-class requirements where road width is equal to or less than the pole height. Added house-side backlight.



TECHNICAL SPECIFICATIONS:

Dimensions	50.0 mm
Height	8.9 mm
Fastening	glue, pin, screw
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
STRADA-2X2-ME-WIDE1	Multi-lens	PMMA	clear	


ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
C14164_STRADA-2X2-ME-WIDE1 » Box size: 480 x 280 x 300 mm	800	160	160	7.9


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.




Isometric view










Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: Up to 30mm class M, otherwise class C. According to DIN ISO 2768-2 Form and position: class L	Ledil Oy Salorankatu 10 FIN 24240 SALO Finland
THIRD ANGLE PROJECTION:	DRAWING TITLE STRADA-2X2-ME-WIDE1
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.	SIZE A4 / PART NUMBER C14164
	SCALE 1:1 / WEIGHT - / SHEET 1/1

PHOTOMETRIC DATA (MEASURED):

CREE

LED	XD16
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




CREE

LED	XD16
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour	White

Required components:






CREE

LED	XP-G
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover




CREE

LED	XP-G2
FWHM	Asymmetric
Efficiency	83 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

CREE

LED	XP-G3
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



CREE

LED	XP-L HD
FWHM	Asymmetric
Efficiency	83 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White


Required components:

Transparent protective cover

CREE

LED	XP-L2
FWHM	Asymmetric
Efficiency	85 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



LG Innotek

LED	H35C1 (LEMWA33)
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON TX
FWHM	Asymmetric
Efficiency	84 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:

Transparent protective cover

LUMILEDS

LED	LUXEON V
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



NICHIA

LED	NVSW219F
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



NICHIA

LED	NVSW319B
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


NICHIA

LED	NVSW3x9A
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover






OSRAM

LED	PrevaLED Brick HP 2x8
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






OSRAM
Opto Semiconductors

LED	Duris S8
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON Square PC
FWHM	Asymmetric
Efficiency	84 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover

PHILIPS

LED	Fortimo FastFlex LED 2x8 DA G4
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



PHILIPS

LED	Fortimo FastFlex LED 2x8 DA G4+
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



PHILIPS

LED	Fortimo FastFlex LED 2x8 DAX G4
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED	HiLOM RH16 (LH351C)
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




SAMSUNG

LED	LH351B
FWHM	Asymmetric
Efficiency	87 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



SAMSUNG

LED	LH351B
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



SEOUL SEMICONDUCTOR

LED	Z5M3
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

SEOUL SEMICONDUCTOR

LED	Z5M4
FWHM	Asymmetric
Efficiency	98 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



SEOUL SEMICONDUCTOR

LED	Z8Y22
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




TOSHIBA
Leading Innovation

LED	TL1L4
FWHM	Asymmetric
Efficiency	83 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover



TRIDONIC

LED	RLE 2x4 2000lm HP EXC2 OTD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White


Required components:

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


TRIDONIC

LED	RLE 2x8 4000lm HP EXC2 OTD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




TRIDONIC

LED	RLE G1 49x121mm 2000lm xxx EXC OTD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




TRIDONIC

LED	RLE G1 49x133mm 2000lm xxx EXC OTD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



TRIDONIC

LED	RLE G1 49x223mm 4000lm xxx EXC OTD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

TRIDONIC

LED	RLE G1 49x245mm 4000lm xxx EXC OTD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

CREE

LED	XHP35 HD
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



CREE

LED	XHP35 HI
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




CREE

LED	XP-G2
FWHM	Asymmetric
Efficiency	80 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



CREE

LED	XP-G2 HE
FWHM	Asymmetric
Efficiency	92 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (SIMULATED):

CREE

LED	XP-G3
FWHM	Asymmetric
Efficiency	78 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



CREE

LED	XP-L HI
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




CREE

LED	XP-L2
FWHM	Asymmetric
Efficiency	80 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover




CREE

LED	XT-E
FWHM	Asymmetric
Efficiency	84 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (SIMULATED):

LUMILEDS

LED	LUXEON 5050 Round LES
FWHM	Asymmetric
Efficiency	86 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



LUMILEDS

LED	LUXEON 5050 Round LES
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LUMILEDS

LED	LUXEON T
FWHM	Asymmetric
Efficiency	84 %
LEDs/each optic	1
Light colour	White


Required components:

Transparent protective cover

NICHIA

LED	NV4WB35AM
FWHM	Asymmetric
Efficiency	95 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

NICHIA

LED	NVSW3x9A
FWHM	Asymmetric
Efficiency	93 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




NICHIA

LED	NVSxE21A
FWHM	Asymmetric
Efficiency	81 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



NICHIA

LED	NVSxx19B/NVSxx19C
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




NICHIA

LED	NVSxx19B/NVSxx19C
FWHM	Asymmetric
Efficiency	82 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (SIMULATED):

OSRAM Opto Semiconductors

LED	Duris S8
FWHM	Asymmetric
Efficiency	81 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


Transparent protective cover



OSRAM Opto Semiconductors

LED	OSCONIQ P 3737 (2W version)
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



OSRAM Opto Semiconductors

LED	OSCONIQ P 3737 (3W version)
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



OSRAM Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM	Asymmetric
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM	Asymmetric
Efficiency	80 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover



SAMSUNG

LED	LH351D
FWHM	Asymmetric
Efficiency	76 %
Peak intensity	0.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Transparent protective cover

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.