

Dual N-Channel 60-V (D-S) MOSFET

Key Features:

- Low $r_{DS(on)}$ trench technology
- Low thermal impedance
- Fast switching speed



Typical Applications:

- White LED boost converters
- Automotive Systems
- Industrial DC/DC Conversion Circuits

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (m Ω)	I_D (A)
60	260 @ $V_{GS} = 10V$	2.0
	330 @ $V_{GS} = 4.5V$	1.8



RoHS
COMPLIANT
HALOGEN
FREE



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Units
Drain-Source Voltage		V_{DS}	60	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ^a	$T_A = 25^\circ\text{C}$	I_D	2.0	A
	$T_A = 70^\circ\text{C}$		1.6	
Pulsed Drain Current ^b		I_{DM}	10	
Continuous Source Current (Diode Conduction) ^a		I_S	1.8	A
Power Dissipation ^a	$T_A = 25^\circ\text{C}$	P_D	1.5	W
	$T_A = 70^\circ\text{C}$		0.95	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS				
Parameter		Symbol	Maximum	Units
Maximum Junction-to-Ambient ^a	$t \leq 10 \text{ sec}$	$R_{\theta JA}$	40	$^\circ\text{C/W}$
	Steady State		90	

Notes

- Surface Mounted on 1" x 1" FR4 Board.
- Pulse width limited by maximum junction temperature

Electrical Characteristics







Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D = 250 \mu A$	1			V
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 V$, $V_{GS} = \pm 20 V$			± 10	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 48 V$, $V_{GS} = 0 V$			1	μA
		$V_{DS} = 48 V$, $V_{GS} = 0 V$, $T_J = 55^\circ C$			25	
On-State Drain Current ^a	$I_{D(on)}$	$V_{DS} = 5 V$, $V_{GS} = 10 V$	3			A
Drain-Source On-Resistance ^a	$r_{DS(on)}$	$V_{GS} = 10 V$, $I_D = 1.5 A$			260	m Ω
		$V_{GS} = 4.5 V$, $I_D = 1.2 A$			330	
Forward Transconductance ^a	g_{fs}	$V_{DS} = 15 V$, $I_D = 1.5 A$		10		S
Diode Forward Voltage ^a	V_{SD}	$I_S = 0.9 A$, $V_{GS} = 0 V$		0.84		V
Dynamic ^b						
Total Gate Charge	Q_g	$V_{DS} = 30 V$, $V_{GS} = 4.5 V$, $I_D = 1.5 A$		1.7		nC
Gate-Source Charge	Q_{gs}			0.5		
Gate-Drain Charge	Q_{gd}			1.0		
Turn-On Delay Time	$t_{d(on)}$	$V_{DS} = 30 V$, $R_L = 20 \Omega$, $I_D = 1.5 A$, $V_{GEN} = 10 V$, $R_{GEN} = 6 \Omega$		3		ns
Rise Time	t_r			4		
Turn-Off Delay Time	$t_{d(off)}$			12		
Fall Time	t_f			3		
Input Capacitance	C_{iss}	$V_{DS} = 15 V$, $V_{GS} = 0 V$, $f = 1 Mhz$		97		pF
Output Capacitance	C_{oss}			11		
Reverse Transfer Capacitance	C_{rss}			7		

Notes


- a. Pulse test: $PW \leq 300 \mu s$ duty cycle $\leq 2\%$.
- b. Guaranteed by design, not subject to production testing.

Analog Power (APL) reserves the right to make changes without further notice to any products herein. APL makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APL assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in APL data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. APL does not convey any license under its patent rights nor the rights of others. APL products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APL product could create a situation where personal injury or death may occur. Should Buyer purchase or use APL products for any such unintended or unauthorized application, Buyer shall indemnify and hold APL and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that APL was negligent regarding the design or manufacture of the part. APL is an Equal Opportunity/Affirmative Action Employer.


Typical Electrical Characteristics




Typical Electrical Characteristics




7. Gate Charge




8. Normalized On-Resistance Vs Junction Temperature



9. Safe Operating Area




10. Single Pulse Maximum Power Dissipation



11. Normalized Thermal Transient Junction to Ambient

Package Information



SYMBOL	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.70	0.75	0.80	0.028	0.030	0.032
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	---	0.20 REF	---	---	0.008 REF	---
b	0.25	0.30	0.35	0.010	0.012	0.014
D	---	2.00 BSC	---	---	0.079 BSC	---
D2	0.60	0.65	0.70	0.024	0.026	0.028
D3	0.60	0.65	0.70	0.024	0.026	0.028
E	---	2.00 BSC	---	---	0.079 BSC	---
E2	0.81	0.86	0.91	0.032	0.034	0.036
G	---	0.65 BSC	---	---	0.026 BSC	---
L	0.25	0.30	0.35	0.010	0.012	0.014
F	---	0.20 REF	---	---	0.008 REF	---
f	---	45°	---	---	45°	---
G	0.15	0.20	0.25	0.006	0.008	0.010
aaa	---	0.15	---	---	0.006	---
bbb	---	0.10	---	---	0.004	---
ccc	---	0.10	---	---	0.004	---
ddd	---	0.08	---	---	0.003	---