

The thinnest possible body contributes to reduced size, height and weight of the set product



Typical Specifications



Items	Specifications
Total resistance tolerance	±20%
Maximum operating voltage	200V AC, 10V DC (RS60N Series) 500V AC, 10V DC (RSA0N Series)
Operating force	0.3 $\pm_{-0.25}^{+0.5}$ N
Operating life	30,000 cycles
Operating temperature range	-10°C to +60°C

Product Line

Number of resistor elements	Travel (mm)	Lever type	Length of lever (mm)	Total resistance (k Ω)	Resistance taper	Terminal style	Minimum order unit (pcs.)		Products No.	Drawing No.
							Japan	Export		
Single-unit	60	4	20	10	1B	For PC board	600	1,200	RS60N11S4006	1
	100	9-T (T-Bar)	8.2				400	800	RSA0N11S9A0K	2

Note

Other varieties are also available. Refer to "Other Specifications" (P.415).

Packing Specifications

Tray

Travel (mm)	Number of packages (pcs.)		Export package measurements (mm)
	1 case /Japan	1 case /export packing	
60	600	1,200	377×517×371
100	400	800	



Dimensions

Unit:mm

No.	Style	PC board mounting hole dimensions (Viewed from mounting side)
1		

Refer to P.415 for other specifications.
Refer to P.416 for ordering products not listed.
Refer to P.426 for soldering conditions.

■ Dimensions

No.		Style	PC board mounting hole dimensions (Viewed from mounting side)
2		 t=1.2	

Low-profile Master Type (Slim Type) / Other Specifications

In addition to the products listed, we can accommodate the follow specifications.




■ Total Resistance Variety

Total resistance (k Ω)	10	50	100	250
--------------------------------	----	----	-----	-----

■ Resistance Taper

Resistance taper	15A	1B	10A
------------------	-----	----	-----


■ Lever Types

Configuration code	1	4	9-T (T-Bar)
Dimensions	 t=1.2	 t=1.2	 t=1.2

■ Corresponding Specification

Dust cover	Available
------------	-----------

■ Terminal Layout / Circuit Diagram



Note

Marked are specifications recommended by Alps.

When ordering product varieties that are not listed, specify referring to the examples below.

Sample Part Number

R S 6 0 N 1 1 S - 0 1 - B 1 0 3

Travel

60	60mm
A0	100mm

Number of resistor elements


Single-unit	1
-------------	---

Lever types

Code	Configuration code
01	1
04	4
9T	9-T (T-Bar)

Resistance taper

Code	Resistance taper
A	15A
B	1B
D	10A



Total resistance

Code	Total resistance (k Ω)	Code	Total resistance (k Ω)
103	10	104	100
503	50	254	250

Slide Potentiometers

List of Varieties

Type		Low-profile master type			Motor-driven master type		
Series		N Fader	Slim Type	Super P Fader	Motor N Fader	Motor K Fader	Motor V Fader
		RS □□ N	RS □□ N1S	RS6011 □ P	RS □□ N1 □ M	RSA0K1 □ V	RSA0V11M
		Single-unit/Dual-unit	Single-unit	Single-unit/Dual-unit	Single-unit/Dual-unit	Single-unit/Dual-unit	Single-unit
Photo							
Travel (mm)		60, 100		60	60, 100	100	100
Direction of lever		Vertical					
Lever material		Metal					Resin
Operating temperature range		−10℃ to +60℃					
Operating life		30,000 cycles			30,000 cycles	300,000 cycles	100,000 cycles
Available for automotive use		—	—	—	—	—	—
Life cycle							
Electrical performance	Total resistance (k Ω)	10, 50, 100, 250		10, 20, 50	10, 50, 100, 250	10	10
	Resistance taper	15A, 1B, 10A			Single-unit: 1B Dual-unit: Servo 1B Audio 15A, 1B, 10A		1B
	Rated Power	0.1W (RS60N) 0.25W (RSA0N)	0.2W (RS60N1S) 0.5W (RSA0N1S)	0.2W (Single-unit) 0.1W (Dual-unit)	0.2W (RS60N1□M) 0.5W (RSA0N1□M)	0.5W	
	Insulation resistance	100MΩ min. 250V DC					
	Voltage proof	250V AC for 1 minute					
	Center-taps	Without					
Mechanical performance	Operating force	Single-unit 0.3 ^{+0.5} _{−0.25} N Dual-unit 0.4 ^{+0.5} _{−0.35} N	0.3 ^{+0.5} _{−0.25} N	0.5 ^{+1.0} _{−0.4} N	0.8±0.5N	Single-unit 0.4±0.25N Dual-unit 0.25 to 0.9N	—
	Center detent	Without					
	Stopper strength	100N					10N
	Lever push-pull strength	50N					5N
	Lever wobble (mm) ※ Both sides	$\frac{2(2 \times L)}{25}$					
	Lever deviation (mm)	0.5 max. (One side)					
Terminal style		Insertion			Lead, Insertion	Connector(Fader) Lead (Motor)	Connector
Page		410	414	417	420		

Slide Potentiometers Soldering Conditions	426
Potentiometer Cautions	427
Potentiometers Measurement and Test Methods	429
Potentiometers Resistance Taper	431

Notes

1. Attenuation is specified for residual resistance.
2. "L" in the "Lever Wobble" column of the above table indicates the length of lever.

Reference for Manual Soldering


Series	Tip temperature	Duration of Soldering time	No. of solders
RS□□1, RS□□H, RS08U, RS□□K (Standard), RS□□N, RS□□N11S, RS6011□P, RS□□N1□M, RSA0K1□V (Motor terminal)	350°C max.	3s max.	1 time

Reference for Dip Soldering

Series	Preheating		Dip soldering		Number of soldering
	Soldering surface temperature	Heating time	Soldering temperature	Soldering time	
RS□□1, RS□□H, RS□□N, RS□□N11S, RS6011□P, RS□□N1□M	100°C max.	1 min. max.	260°C	5s max.	1 time

Example of Reflow Soldering Condition

Temperature profile



Series	A	B	C	D	E	F	G	H	No. of reflows
RS08U	250°C	200°C	150°C	150°C	2 min.	3s	40s	4 min.	1 time

Notes

1. When using an infrared reflow oven, solder may sometimes not be applied. Be sure to use a hot air reflow oven or a type that uses infrared rays in combination with hot air.
2. The temperatures given above are the maximum temperatures at the terminals of the potentiometer when employing a hot air reflow method. The temperature of the PC board and the surface temperature of the potentiometer may vary greatly depending on the PC board material, its size and thickness. Ensure that the surface temperature of the potentiometer does not rise to 250°C or greater.
3. Conditions vary to some extent depending on the type of reflow bath used. Be sure to give due consideration to this prior to use.