



Pin Define	
P1	SWITCH TERM CD
P2	DAT1
P3	DAT0
P4	VSS
P5	CLK
P6	VDD
P7	CMD
P8	CD/DAT3
P9	DAT2
P10	GND
P11	GND
P12	GND

Specification

***Electrical Characteristics:**

Contact Current Rating:0.5Amperes.
 Dielectric Withstanding Voltage:AC500V r.m.s.
 Insulation Resistance:1000 Megohms
 Minimum At DC 500V.
 Contact Resistance:100 mΩ Maximum.

***Mechanical Characteristics:**

Mating Cycles:10,000 Cycles.

***Environmental:**

Operating Temperature:-25°C~+85°C.

***Materials:**

Insulator:HI-Temp plastic UL 94V-0 Rated.
 Contact:Copper Alloy.
 Shell:Stainless Steel(t=0.15mm).



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: TF PUSH 板下沉板1.35
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HWCW143-TF09-135B
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2206011552
			SHEET NO. 1 OF 1