



Screw Connectors

230/11 DS

Terminal Block, 11 pole, Insulating Material: PA 6, Cross-Section: 2.5 mm², Pin Spacing: 8.0 mm, Wire Protector (DS): yes, Fixing: Screw, Voltage Rating: 450 V, Current Rating: 24 A



Order Info

| | |
|------------------------------------|---|
| Reference Number (ref. no.) | 121311 |
| Applications | Lighting, Installation, Electrical Appliances |
| PU | 200 |
| EAN | 4028012133420 |

Type

| | |
|--------------------------------|---------------------|
| Type | Terminal Block |
| Number of poles | 11 pole |
| Clamping Units per Pole | 1 |
| Colour | natural |
| Cross-Section | 2.5 mm ² |
| Connection Type | Screw |
| Wire Protector (DS) | yes |

Technical Data

| | |
|---|--|
| Voltage Rating | 450 V |
| Current Rating | 24 A |
| Insulating Material | PA 6 |
| Contact Material | Brass |
| Core Cross-Section min. | 0.5 mm ² |
| Core Cross-Section max. | 2.5 mm ² |
| Flammability Rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| Type of Conductor Solid | yes |
| Type of Conductor Flexible | yes |
| Type of Conductor Stranded | yes |
| Stripping Length | 5.0-5.5 mm |
| Assembly Contact Screw | 0.8x4.0 / ⚙ 0.5 Nm |
| Pin Spacing | 8.0 mm |
| Fixing | Screw |
| Approbation EN60998 | 200_230_EN60998_20012012_VDE_ENEC_40034813_web.pdf |
| Approbation UL | 230_19820924_20120103_UL_E63492_1-02_Description_web.pdf |

Accessories

230 BZ/11

191211

ZEL 110

196420
