

## Han F+B 17D SMC MI CRT



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 517 3001
Specification	Han F+B 17D SMC MI CRT
HARTING eCatalogue	<a href="https://b2b.harting.com/09155173001">https://b2b.harting.com/09155173001</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> F+B

### Version

Termination method	Crimp termination
Gender	Male
Number of contacts	17
PE contact	Yes
Details	Please order crimp contacts separately.

### Technical characteristics

Conductor cross-section	0.14 ... 2.5 mm <sup>2</sup>
Rated current	10 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500
Mating cycles with other HMC components	≥3,000

### Material properties

Material (insert)	Polycarbonate (PC)
-------------------	--------------------



Pushing Performance

## Material properties

Colour (insert) RAL 7032 (pebble grey)

Material flammability class acc. to UL 94 V-0

## Commercial data

Packaging size 1

Net weight 16 g

Country of origin China

European customs tariff number 85389099

eCl@ss 27440205 Contact insert for industrial connectors