



C1733





tyco Electronics

Product Description

**ADSL Line Coupling Transformer, IEC60950 Supplementary 250V
450 μ H, 1.80 : 1.00 (Line : IC), SMD EP13**



Customer to determine PCB pad dimensions.



Primary units are in inches. Millimeters are in brackets.

Electrical Specifications at +20°C unless noted otherwise

Test Description	Limit	Units	Tol	Notes
Inductance	450.0	μ H	5.0%	1-4 tie(3+2), 10kHz, 100mVAC, Ls.
Leakage Inductance	5.50	μ H	Max.	1-4 tie(3+2, 8+9, 10-7), 100kHz, 100mVAC, Ls.
DC Resistance	0.250	Ω	Max.	10-8
DC Resistance	0.800	Ω	Max.	1-3
DC Resistance	0.800	Ω	Max.	2-4
DC Resistance	0.300	Ω	Max.	9-7
Turns Ratio	1.80	---	1.00%	(1-4) : (10-7) tie(8+9, 2+3), 10KHz, 100mVAC.
Dielectric	1875	VAC	500 μ A	1-10 tie(2+3, 8+9), 1 second test, 500 μ A maximum leakage current.
Total Harmonic Distortion	-95	dB	Typ.	40KHz, 2.5Vrms [7.07 Vp-p], Line : IC
Insertion Loss	0.300	dB	±0.20	100kHz.
Frequency Response	±1.2	dB	Typ.	100kHz Reference.
Longitudinal Balance (ITU)	-40	dB	Min.	20kHz - 1.1MHz, Gnd pin 10 or 7.

Agency Approvals

BABT	Certificate No. NC/000166	Japan (via CB Cert.)	Certif. No. GB551W
UL1950	File E189690	Austel (via CB Cert.)	Certif. No. GB551W
CSA 950 (via UL/CUL)	File E189690	Sweden (via CB Cert.)	Certif. No. GB551W
IEC 60950 (via CB Cert.)	Certificate No. GB551W	Norway (via CB Cert.)	Certif. No. GB551W

BABT

The information contained in this drawing is the sole property of CoEv, Inc. Any reproduction or use without the written permission of CoEv, Inc. is prohibited.

TEL 888-978-2638 - FAX 605-886-8995 - www.coev.net