


Servo motor EMMS-AS-100-LK-HV-RRB

Part number: 1562993

FESTO



Data sheet

Feature	Value
Number of pole pairs	6
Type code	EMMS-AS
Rotor position sensor	Resolver
Rotor position sensor interface	SIN/COS analog signals
Rotor position sensor measuring principle	Inductive
Temperature monitoring	PTC resistor
Max. rotational speed	4040 1/min
Nominal rotary speed	3400 1/min
Brake DC operating voltage	24 V
Insulation protection class	F
Brake power consumption	18 W
Motor constants	1.66 Nm/A
Nominal operating voltage DC	565 V
Motor nominal power	2240 W
DC nominal voltage	565 V
Motor nominal current	3.79 A
Phase-phase winding resistance	1.98 Ohm
Winding inductance phase-phase	7.76 mH
Type of winding switch	Star inside
Peak current	24.8 A
Voltage constant, phase-to-phase	98.93 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 90 %
Degree of protection	IP54
Ambient temperature	-40 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	7.34 kgcm ²
Brake holding torque	9 Nm
Brake mass moment of inertia	0.54 kgcm ²
Nominal torque	6.29 Nm
Peak torque	35.4 Nm

Feature	Value
Stall torque	10.93 Nm
Permissible axial shaft load	150 N
Permissible radial shaft load	650 N
MTTF, subcomponent	114 years, rotor position sensor 3356 years, holding brake
MTTFd, subcomponent	228 years, rotor position sensor
Switching cycles, holding brake	10 million idle actuations (without friction work!)
Product weight	9630 g
Electrical connection technology	Plug
Note on materials	RoHS-compliant
Conforms to standard	IEC 60034
Featherkey shaft design	DIN 6885 A 6 x 6 x 32