
Bi-directional ESD Protection Diode

FEATURES

- Meet IEC61000-4-2 (ESD) ±15kV (air), ±8kV (contact)
- Meet IEC61000-4-4 (EFT) rating. 40A (5/50ns)
- Protects one Bi-directional I/O line
- Working Voltage : 5V
- Pb free version and RoHS compliant
- Packing code with suffix "G" means
  green compound (halogen-free)



SOD-323



MECHANICAL DATA

- Case: SOD-323 small outline plastic package
- Terminal: Matte tin plated, lead free., solderable
  per MIL-STD-202, Method 208 guaranteed
- High temperature soldering guaranteed : 260°C/10s
- Weight: 4.85 ± 0.5 mg
- Marking code: AC

APPLICATIONS

- Cell Phone Handsets and Accessories
- Notebooks, Desktops, and Servers
- Keypads, Side Keys, USB 2.0, LCD Displays
- Portable Instrumentation
- Microprocessor Based Equipment

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Peak Pulse Power (tp=8/20μs waveform)	P_{PP}	350	W
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	± 15 ± 8	KV
Junction and Storage Temperature Range	T_J , T_{STG}	-55 to +150	°C

PARAMETER		SYMBOL	MIN	MAX	UNIT
Reverse Stand-Off Voltage		V_{RWM}	-	5	V
Reverse Breakdown Voltage	I_R = 1 mA	$V_{(BR)}$	6	-	V
Reverse Leakage Current	V_R = 5 V	I_R	-	5	μA
Clamping Voltage	I_{PP} = 1 A	V_C	-	9.8	V
	I_{PP} = 8 A		-	18.3	
Junction Capacitance	V_R = 0 V , f = 1.0 MHz	C_J	1.2		pF

RATINGS AND CHARACTERISTICS CURVES

(T_A=25°C unless otherwise noted)

Fig. 1 Non-Repetitive Peak Pulse Power VS. Pulse Time




Fig. 2 Pulse Waveform




Fig. 3 Admissible Power Dissipation Curve




Fig. 4 Typical Junction Capacitance






Fig. 5 Clamping Voltage VS. Peak Pulse Current




Small Signal Product

ORDER INFORMATION (EXAMPLE)




PACKAGE OUTLINE DIMENSIONS

SOD-323



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	**Min**	**Max**
A	1.150	1.400	0.045	0.055
B	2.300	2.700	0.091	0.106
C	0.250	0.450	0.010	0.018
D	1.600	1.800	0.063	0.071
E	0.800	1.000	0.031	0.039
F	0.050	0.177	0.002	0.007
G	0.475 REF		0.019 REF	
H	-	0.100	-	0.004

SUGGEST PAD LAYOUT



DIM.	Unit (mm)	Unit (inch)
	Min	**Min**
G	1.52	0.060
X	0.59	0.023
X1	2.70	0.106
Y	0.45	0.018

Note: The suggested land pattern dimensions have been provided for reference only, as actual pad layouts may vary depending on application.

APPLICATION INFROMATION

- Designed to protect one data, I/O, or power supply line
- Designed to protect sensitive electronics from damage or latch-up due to ESD
- Designed to replace multilayer varistors (MLVs) in portable applications
- Offers superior electrical characteristics such as lower clamping voltage and no device degradation when compared to MLVs
- The combination of small size and high ESD surge capability makes them ideal for use in portable applications

CIRCUIT BOARD LAYOUT RECOMMENDATIONS

- Good circuit board layout is critical for the suppression of ESD induced transients
- Place the ESD Protection Diode near the input terminals or connectors to restrict transient coupling
- Minimize the path length between the ESD Protection Diode and the protected line
- Minimize all conductive loops including power and ground loops
- The ESD transient return path to ground should be kept as short as possible

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied,to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or seling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.