General Specifications

Electrical Capacity

Resistive Load: 10A @ 125V AC or 6A @ 250V AC
Motor Load: 400W @ 125V AC
Lamp Load: 2A @ 125V AC for On-Off-On circuit & 3A @ 125V AC for other circuits

Other Ratings

Contact Resistance: 10 milliohms maximum
Insulation Resistance: 1,000 megohms minimum @ 500V DC
Dielectric Strength: 2,000V AC minimum between contacts for 1 minute minimum;
4,000V AC minimum between contacts & case for 1 minute minimum
Mechanical Life: 100,000 operations minimum
Electrical Life: 25,000 operations minimum
Angle of Throw: 25°

Materials & Finishes

Toggle Cap: Brass with nickel plating
Lever: Brass with chrome plating
Bushing: Brass with nickel plating
Frame: Stainless steel
Case/Base: Diallyl phthalate resin (UL94V-0)
Movable Contacts: Silver alloy with silver plating
Stationary Contacts: Pure silver with silver plating
Terminals: Copper with silver plating

Environmental Data

Operating Temp Range: –10°C through +85°C (+14°F through +185°F)
Humidity: 90 ~ 95% humidity for 96 hours @ 40°C (104°F)
Vibration: 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock: 50G (490m/s^2) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

Installation

Soldering Time & Temp: Wave Soldering Recommended (Straight PC): See Profile A in Supplement section.
Manual Soldering: See Profile A in Supplement section.
Cleaning: These devices are not process sealed. Hand clean locally using alcohol based solution.

Standards & Certifications

Flammability Standards: UL94V-0 rated case/base
UL: **File No. E44145 - Recognized only when ordered with marking on switch.**
Add "/U" or "/CUL" to end of part number to order UL recognized switch.
All models recognized at 10A @ 125V AC & 6A @ 250V AC.

CSA: **File No. 023535_0_000 - Certified only when ordered with marking on switch.**
Add "/C" to end of part number to order CSA certified switch.
All models certified at 10A @ 125V AC & 6A @ 250V AC.

VDE: **License No. 119174**
All models approved at 10A @ 125V AC & 6A @ 250V AC.
Marking on switch is standard. All models meet EN 61058-1 standard.

Distinctive Characteristics

Meets EN 61058-1 standard.

High torque bushing construction prevents rotation or separation from frame during installation.

Stainless steel frame resists corrosion and increases environmental safety.

Case/base of heat resistant resin meets UL94V-0 flammability standard.


Contacts of special silver alloy resist arcing and guarantee stable electrical contact and long life.

High insulating barriers increase isolation of circuits in double pole devices and provide added protection to contact points.


Prominent external insulating barriers increase insulation resistance and dielectric strength.

Epoxy sealed terminals prevent entry of flux, solvents, and other contaminants.

Clinching of the frame to the case well above the base and terminals provides 4,000V dielectric strength.



Actual Size



TYPICAL SWITCH ORDERING EXAMPLE

P20 | 22 | B | [ ]

Poles & Circuits

11	SPST	ON	NONE	OFF
12	SPDT	ON	NONE	ON
13	SPDT	ON	OFF	ON
21	DPST	ON	NONE	OFF
22	DPDT	ON	NONE	ON
23	DPDT	ON	OFF	ON

Toggles & Bushings

No Code	.512″ (13.0mm) White Cap with 6mm Bushing
E	.450″ (11.4mm) Flatted with 6mm Bushing
B	.689″ (17.5mm) Large Bat with 12mm Bushing
D	.748″ (19.0mm) White Capped Column with 12mm Bushing


Terminals

No Code	Solder Lug*
P	Straight PC
Z	.187″ (4.75mm) Quick Connect

* Wire harness & cable assemblies offered only in Americas

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE




P2022B



IMPORTANT:


VDE is marked on all models. Switches are supplied without UL, cULus & CSA marking unless specified. **UL, cULus & CSA recognized only when ordered with marking on the switch.** Specific models, ratings, & ordering instructions are noted on General Specifications page.

POLES & CIRCUITS


		Toggle Position			Connected Terminals			Throw & Schematics
Pole	**Model**	**Down** (Keyway)	**Center**	**Up**	**Down** (Keyway)	**Center**	**Up**	Note: Terminal numbers are on the switch.
SP	**P2011**	ON	NONE	OFF	1-1b	OPEN	OPEN	SPST 
SP	**P2012** **P2013**	ON ON	NONE OFF	ON ON	1-1b	OPEN	1-1a	SPDT 
DP	**P2021**	ON	NONE	OFF	1-1b 2-2b	OPEN	OPEN	DPST 
DP	**P2022** **P2023**	ON ON	NONE OFF	ON ON	1-1b 2-2b	OPEN	1-1a 2-2a	DPDT 

TOGGLES & BUSHINGS


No Code **.512" (13.0mm) White Cap with 6mm Bushing**




E **.450" (11.4mm) Flatted with 6mm Bushing**



B **.689" (17.5mm) Large Bat with 12mm Bushing**




D **.748" (19.0mm) White Capped Column with 12mm Bushing**




Panel Cutouts


Panel Thickness with Keyway .134" (3.4mm) maximum




Panel Thickness with Locking Ring .102" (2.6mm) maximum



Panel Thickness with Keyway .256" (6.5mm) maximum



Panel Thickness with Locking Ring .217" (5.5mm) maximum




Standard Hardware


For 6mm Bushing: 1 Locking Ring AT507M, 1 Internal Tooth Lockwasher AT509, 2 Hex Nuts AT513M
For 12mm Bushing: 1 Hex Face Nut AT503M, 1 Locking Ring AT506M, 1 Internal Tooth Lockwasher AT508, 1 Hex Mounting Nut AT527M
Optional Splashproof Boot Assemblies (for code B): AT401 & AT4181 boots plus hex nut & o-ring; see Accessories & Hardware section.

TERMINALS


No Code **Solder Lug**




Z **.187" (4.75mm) Quick Connect**




P **Straight PC**




SPST




SPDT



DPST




DPDT





TYPICAL SWITCH DIMENSIONS

P2011, P2012, P2013

6mm Bushing











P2011 models do not have terminal 1a.


P2012

P2021B, P2022B, P2023B

12mm Bushing









P2021 models do not have terminals 1a & 2a.

P2022B