


- NOTES:
- MATERIAL:
    - HOUSING: LCP ,COLOR IS BLUE;
    - CONTACT: BRASS (H65 T=0.20&0.25mm);
    - SHELL: COLD ROLLED IRON (SPCC T=0.30mm);
  - ELECTRICAL:
    - VOLTAGE RATING: 30V DC ;
    - CURRENT RATING: 1.5A ;
    - CONTACT RESISTANCE: 30MILLIOHMS MAX.;
    - WITHSTAND VOLTAGE: 100V AC RMS 50(60)Hz,1MIN.;
    - INSULATION RESISTANCE: 100MEGOHMS MIN @500V DC;
  - MECHANICAL:
    - MATING FORCE: 35N MAX.;
    - UNMATING FORCE: 5~35N ;
    - OPERATING LIFE: 1500 CYCLES MIN.;
  - PLATING:
    - TERMINAL:
      - NI PLATING OVER ALL,
      - Tin PLATING ON SOLDER AREA,
      - Au G/Fu" ON CONTACT AREA;
    - SHELL: NI PLATING OVER ALL;
  - ENVIRONMENTAL:
    - STORAGE TEMPERATURE RANGE: -40°C~+85°C;
    - OPERATION TEMPERATURE RANGE: -25°C~+70°C;

PIN NUMBER	SIGNAL NAME
PIN 1	Vbus
PIN 2	D-
PIN 3	D+
PIN 4	GND
PIN 5	StdA_SSRX-
PIN 6	StdA_SSRX+
PIN 7	GND_DRAIN
PIN 8	StdA_SSTX-
PIN 9	StdA_SSTX+
SHELL	GND

			GENERAL TOLERANCE	制图 DRAWING	 <b>深圳市华灿天禄电子有限公司</b> ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审核 CHECK				
			X.X ±0.30	批准 APPROVAL	产品名称 TITLE	TYPE AF 9P 3.0 180° L15.0mm 直脚 卷边	版本 REV.	A
			X.XX ±0.20	比例 SCALE	产品料号 PART NO.	HC-ST-003-010-L15.0-J	单位 UNITS	mm
			X.XXX ±0.10	投影 Projection	材料 MATERIAL		页次 SHEET	1/1
1	初版发行		Angle ±3.0°					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE						