



Nut Torque: 5 ~ 14Nm  
 Operating Pressure: 300gf ±100gf  
 Operating Stroke: 0.6mm±0.3mm  
 Protection Grade: IP67, IK08  
 Function: (ON)-OFF  
 Contact: Silver Alloy  
 Base: PA66  
 Shell: SUS  
 Button: SUS  
 Rating: 50mA 48V DC  
 Contact Resistance: 50mΩ MAX.  
 Insulation Resistance: 100MΩ MIN.  
 Dielectric Strength: 1500VAC 1 minute  
 Electrical life: 50,000 cycles  
 Mechanical life: 200,000 cycles  
 Operating Temperature: -20°C~80°C  
 Relative Air Humidity: 45%~85%  
 Safety Approval:



公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECON NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
						孙成	PBM-30Q12-FT-U4-R6-S7S-A3	PBM-30Q12+FT-U4-R6-S7S-A3_A0