

TYPE: _____ QUANTITY: _____ PROJECT: _____

CATALOG
NUMBER:

FIXTURE

WATTAGE

VOLTAGE


FINISH

OPTION

OPTION

OPTION

OPTION



Ceiling pendant luminaire with a choice of frosted acrylic refractor or an anodized aluminum reflector with two part inner surface treatment. Upper etched surface combined with multi-faceted specular lower part. Optional attachments and accessories are available to adapt each luminaire to particular design requirements.

- 1- Standard heavy duty 45° hang straight swivel, with 5" dia. (127) canopy and universal mounting plate.
- 2- 7/8" Dia. (22) X 36" Lg. (914) suspension stem. Precut factory stems are available on request. (Specify STM with desired length)
- 3- Cast aluminum removable top cover for quick maintenance.
- 4- Extruded aluminum ballast housing module with a fine linear stria pattern.
- 5- Set of four aluminum perforated decorative arms.

TR1301: Frosted acrylic refractor.

TR1306: Aluminum reflector.

Inner surface: High performance multi-faceted specular anodized.
Exterior surface: Satin anodized natural aluminum.
Alternate exterior finish (Option RP9)

TR1301



TR1306



MATERIALS

Torx is made of an extruded aluminum ballast housing designed to optimize functionality of electrical components.

Torx is available with a choice of two interchangeable reflectors.

- A frosted acrylic refractor with a linear peripheral pattern providing general upward illumination with efficient down lighting.
- An aluminum reflector designed to optimize light source performance and uniformity.

ELECTRICAL

METAL HALIDE

BALLAST Electronic 120/277V multi volt or 347V (50-60HZ) with a minimum starting temperature of -22°F/-30°C including end of life protection.

SOCKET Medium base pulse rated 4kV porcelain body with a nickel plated screw shell and center contact rated 600V. Supplied with 200°C leads.

COMPACT FLUORESCENT (CFL)

BALLAST Electronic 120/277V multi volt, or 347V (50-60HZ) with end of life protection. Minimum starting temperature of 0°F/-18°C.

SOCKET Thermoplastic body rated for 75W-600V. Supplied with 105°C leads.

FINISH

Polyester powder coating is applied through an electrostatic process and oven cured for long term finish.

MOUNTING

Maximum weight: 12.5lbs (5.7kg)


Mounts on a standard 4" (102) octagonal electrical box with 3 1/2" (89) C/C mounting holes.

CERTIFICATION

Tested to UL1598 and CSA 22.2 #250. ETL listed damp location.

CE certification on request.

Rated IP41.



TR1301/TR1306 SERIES

TORX 12" - HID/CFL

OPTIONS

MOUNTING



STM

Factory cut to size stems up to 144" lg. (Specify length with STM option suffix. Longer stems are available with coupling. Please consult factory.) 36" lg. Standard stems can be shortened on site.



SPG


4/18 X 36" lg. Silver braided power cable C/W on site adjustable suspension cable. Longer suspension available on request.

ACCESSORIES



L14T

Flat bottom frosted acrylic lens with 3" dia. center opening.



Exterior same color as luminaire

TR1306 Only

RP9


Inner reflector specular aluminum. Exterior same color as luminaire.



NP13

Non perforated side aluminum arms.

ELECTRICAL



EM


1 lamp (26/32/42W) 90 mnts. Integral emergency battery back-up. Overall dimension is increased by 2" (50) from nominal std. length to accommodate EM ballast.
1X32W 575 Lumens
1X42W 750 Lumens
120/277V only.

Standard connection:

Test switch and indicator light are installed with luminaire. Factory pre wired for unswitched luminaire. 57W and 70W available with remote EM ballast on request.

Option UH: Uniform OAL with non EM ballast luminaire for same installation is available. All Non EM Luminaires will be increased by 2".

ELECTRICAL




QRS

Quartz restrike standby lamp kit. Power failure: The quartz lamp is energized. Power is restored: Quartz lamp will shut off as H.I.D. Light resumes to full light emission. Max. 100W DC Bayonet base. (Lamp is not included.) (Not applicable with CFL lamps)




QS

BA15d DC bayonet socket (Quartz lamp not included.) 120V Emergency input power. Separate dedicated wiring for external control. May be used for H.I.D or CFL lamps. Max. 100W.



DS1

Luminaire with 2 lamps. Each lamp is separately controlled externally. This option requires 1 ballast per lamp
2X32w
2X42w
2X57w
2X70w



DM4 (Mark X)


2X57W 120V or 277V dimming ballast. Controlled externally. This option requires 1 ballast per lamp

DM1/DM2/DM3 (Mark X)

One dimming ballast for one or two lamps. Mark VII Dimming ballast on request.

DMY

Other types of ballasts or dimming ballasts such as 0-10V Mark VII or Lutron or other brands are available. Please specify ballast type with DMY option suffix. (Some restrictions may apply)



LUMINIS

LUMINIS | Toll free: 866.586.4647 Fax: 514.683.8872
260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

Luminaires may be altered for design improvement or discontinued without prior notice. Unless specified, lamps are not included with luminaires.

LUMINIS.COM

Feb 2016 Rev.0