SHEET 1 OF 1











NOTES:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: x.x=± 0.4mm
   x.xx=± 0.25mm
3. RATING: DC 30V, 0.3A
4. OPERATING FORCE: 200 ± 100gf
5. TRAVEL: 3.3mm FULL TRAVEL (B)
6. LIFE CYCLES: 10,000 CYCLES
7. OPERATING TEMPERATURE: -20˚C TO 70˚C
8. CONTACT RESISTANCE: 20 Milli-ohms MAX.
9. INSULATION RESISTANCE: 100 Mega-OHMS MIN@ 500VDC.
▲ 10. LED COLOR: YELLOW / BLUE
11. ▲ DENOTES CRITICAL PARAMETER.
12. 2002/95/EC (RoHS) COMPLIANT.

LED SPECS	UNITS	YELLOW	BLUE
FORWARD CURRENT	mA	20	20
FORWARD VOLTAGE @20mA	V	1.7 Typ-2.6 Max	3.5 Typ - 4.0 Max
LUMINOUS INTENSITY @ 10mA	MCD	4.7	350

REV	PCR NO	DESCRIPTION	DATE	BY
C	19872	EDIT LED CIRCUIT	4/25/11	BGL
B	19529	DRAWING UPDATE / CLEAN UP	12/14/10	BGL
A	19470	Release For Production	11/29/10	BMA

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E•SWITCH™

TITLE WBL2UOAYBQ

SCALE	DATE	DR	DWG	REV
2	11/29/2010	BMA	B400006	C