

Han Power-T Multi Han Q4/2 tg



Image is for illustration purposes only. Please refer to product description.

Part number	61 88 203 0025 00
Specification	Han Power-T Multi Han Q4/2 tg
HARTING eCatalogue	https://b2b.harting.com/6188203002500

Identification

Category	Energy distributors
Series of hoods/housings	Han-Power [®] T
Element	Energy distributor
Specification	With 5x Han [®] Q 4/2 in Han-Compact [®] Housings, bulkhead mounting

Version

Number of contacts	4
further contacts	+ 2 additional signal contacts
PE contact	Yes

Technical characteristics

Rated current	17 A
Rated voltage conductor-earth	400 V
Rated voltage conductor-conductor	690 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated current (signal)	2 A
Rated voltage (signal)	24 V
Rated impulse voltage (signal)	4 kV
Pollution degree (signal)	3
Rated voltage acc. to UL	600 V
Rated voltage acc. to UL (signal)	24 V



Pushing Performance

Technical characteristics

Rated voltage acc. to CSA	600 V
Rated voltage acc. to CSA (signal)	24 V
Insulation resistance	$>10^8 \Omega$
Limiting temperature	-40 ... +40 °C
Mating cycles	≥ 500
Degree of protection acc. to IEC 60529	IP65

Material properties

Material (contacts)	Copper alloy
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Polyamide (PA)
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Specifications and approvals

Specifications	EN 60664-1 IEC 61984
----------------	-------------------------

Commercial data

Packaging size	1
Net weight	1,388 g
Country of origin	Germany
European customs tariff number	85444290



Pushing Performance

Commercial data

eCl@ss

27142409 Small distribution board