
Product data sheet Characteristics

8502SEG1V07

NEMA Contactor, Type S, nonreversing, Size 3, 90A, 1 phase, up to 100 kA, 2 pole, 600 VAC coil, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility





Main

Product Type	Contactor	e pro-	
Туре	8502S		
Control Circuit Type	Common control circuit	ility o	
Control Circuit Voltage	600 V AC 60 Hz 550 V AC 50 Hz	or reliab	
Contactor Type	Non-reversing	ability	
Current Rating	90 A	Suite	
Number of Poles	2P		
Phase	1 phase	ete	
Horsepower Rating	Not rated		
Maximum Voltage Rating	600 V AC	pesn	
SCCR	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	substitute for and is not to be used for determining suitability or reliability of these pro-	
Control Units	No control units		
Pilot Light	No indicator		
Auxiliary Contacts	Without		
Control Circuit Fusing	Fuse not supplied		
Electrical Connection	Screw clamp terminals	ot in	
Enclosure Type	NEMA 1 painted sheet steel		
Certifications	UL listed file E78351 CCN NLDX CSA	er: This documentation is not intended as	
NEMA Size	3		
Height	21.81 in (554 mm)		
		<u> </u>	

Disclaimer: This documer

7.99 in (203 mm)		
11.46 in (291 mm)		
21193 - 8502,36 SE,SF(NOT S*R,T,W)		
CP1		
1		
15 lb(US) (6.80 kg)		
No		
MX		
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Declaration		
Not compliant		
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		

Contractual warranty

•		
Warranty	18 months	