



KVM-8901US 1

## 19" Widescreen LCD KVM Rack Console

The LevelOne KVM-8901 is a compact and modular KVM console drawer designed to be used in a standard 19-inch server rack. It offers connectivity to 8 or 16 computers by depending on the LevelOne KVM module that is installed (KCM-0832 or 1632). It features a 19-inch retractable LCD(19:10) high video quality up to 1440 x 900 monitor and keyboard with built-in touchpad. Users can daisy chain up to eight units of KCM-0832/1632 together, providing control of up to 128 computers in total, support Auto Scan Mode for monitoring PCs and flexible and easy PC selection via KVM-OSD manual or hot Keys.



1. KCM Moudule Connector

### Key Features

- Modular design for optional KVM switches, enabling management of up to 128 computers
- 1600x1200 resolution
- PS/2 & USB keyboard/mouse support
- On-Screen Display (OSD) for menu navigation
- Support for multiple PC selection methods
- Support for multiple PC selection methods
- Support for multiple PC selection methods
- Support for multiple PC selection methods



### System Specifications

#### Connectors and Cabling:

- DC Jack
- HDB15 Female (Combo)

**Button:**

Auto, Menu, Down, up, Power On/Off

**Indicator:**

Power

**Resolution:**

1440x900 / 1366x768 (16:10 / 16:9)

**Power:**

Power Consumption: 19.2W

Power Input: 12V DC External Power Supply

**Display:**

19" Widescreen TFT LCD Panel

Panel Resolution 1440 x 900

View Angle:H 85 / 85,V 85 / 85

Contrast:500

Brightness:250cd/m<sup>2</sup>

Support Colors:16.7M

**Keyboard / Mouse:**

105 key Keyboard, compatible to IBM PC/AT, PS/2 keyboard, supports Windows function keys

PS/2 Touchpad (Microsoft mouse compatible with PS/2 mouse interface)

Full Wheel Mouse emulation. Left, middle and right button emulation

## Features

**General:**

Sun Micro System Multi-Sync Supported.

Sun Micro System 1152x900 Resolution Supported.

Automatic flat panel shut-off when monitor is in the closed position, or no signal input.

Built-in 8 languages OSD controls

**Management:**

Panel Control and OSD Function

## Environment

**Temperature (°C):**

Operating: 0°C ~ 50°C

Storage: - 20°C ~ 60°C

**Humidity (Non-condensing):**

Storage: 10% ~ 90%

Operating: 10% ~ 90%

## Physical Specifications

**Dimensions (W x D x H mm):**

482 x 610 x 44 mm


**Weight (g):**

20000 g

## Others

**Approval and Compliance:**

CE, FCC, Rohs, REACH



## Order Information

KVM-8901US: US Keyboard  
KVM-8901DE: DE Keyboard  
KVM-8901FR: FR Keyboard  
KVM-8901UK: UK Keyboard

## Package Contents

KVM-8901US  
Power Adapter  
Power Cord  
Quick Installation Guide  
Resource CD (User Manual, QIG)  
KVM Cable  
Screw Kit



**ACC-2101**  
1.8m PS/2 and USB KVM Cable



**ACC-2102**  
3m PS/2 and USB KVM Cable



**ACC-2103**  
5m PS/2 and USB KVM Cable



**KCM-0832**  
8-Port KVM Switch Module



**KCM-1632**  
16-Port KVM Switch Module

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.