


ZWD150PAF-0524/JA



Sales Region	Worldwide
Series	ZWD-PAF
Status	Production
Feature	Peak power capability
Option	JST connector type With cover type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	82% Typ.
Rated Output Voltage[DC]	<u>5V</u> <u>24V</u>
Output Voltage Range[DC]	<u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u>
Minimum Output Current	
Maximum Output Current	<u>5A</u> <u>6A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	150W
Total Maximum Peak Power	294W

Cases Shape & Size

Case'□' shape	PC board
Width(W)	95mm Nom.
Height(H)	51mm Nom.
Depth(D)	252mm Nom.
Weight	885g Typ.

Other

Operating Temp. Range	-10 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
	EN50178
Safety Standard(Conformed)	Den-an

