


技术参数 SPECIFICATIONS

- 线数 (Poles) : 1、2、3、4、6、8
- 适用线规 (Applicable wires) : AWG20#~14#
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 15A Max
- 接触电阻 (Contact resistance) : $\leq 0.01\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 2000V.Ac/1min
- 材料 (Material) :
 插头 (Plug housing) : 尼龙 (PA66) UL94V-2(0)
 插座 (Receptacle housing) : 尼龙 (PA66) UL94V-2(0)
 端子 (Terminal) : 黄铜(Brass Tin/plated)


端子 TERMINAL

型号 Type	适用线规 Applicable wires	电线外径 O.D of wire ins	数量 Quantity
	mm / AWG#	mm	
HX63090-PT	0.52~2.1	20~14	2000PCS/盘
HX63090-RT	0.52~2.1	20~14	5000PCS/盘

HX63090-PT(DJ621-B6.3A-B)



HX63090-RT(DJ611-6.3A-B)



线数 (Poles)	额定电压 (Voltage rating)	额定电流 (Current rating)	插头 (Plug housing)	插座 (Receptacle housing)
1	300V	15A	<p>HX63090-1P(DJ7011-6.3-21)</p>	<p>HX63090-1R(DJ7011-6.3-11)</p>
2	300V	15A	<p>HX63090-2P(DJ7021-6.3-21)</p>	<p>HX63090-2R(DJ7021-6.3-11)</p>
2	300V	15A	<p>HX63094-2P</p>	<p>HX63094-2R</p>

线数 (Poles)	额定电压 (Voltage rating)	额定电流 (Current rating)	插头 (Plug housing)	插座 (Receptacle housing)
3	300V	13A	<p>HX63090-3P(DJ7031-6.3-21)</p>	<p>HX63090-3R(DJ7031-6.3-11)</p>
4	300V	12A	<p>HX63090-4P(DJ7041-6.3-21)</p>	<p>HX63090-4R(DJ7041-6.3-11)</p>
6	300V	12A	<p>HX63090-6P(DJ7061-6.3-21)</p>	<p>HX63090-6R(DJ7061-6.3-11)</p>
8	300V	12A	<p>HX63090-8P(DJ7081-6.3-21)</p>	<p>HX63090-8R(DJ7081-6.3-11)</p>