

Features

- High Surge Capability
- Types up to 600 V V_{RRM}

DO-5 Package

Note:

1. Standard polarity: Stud is cathode.
2. Reverse polarity (R): Stud is anode.
3. Stud is base.



Maximum ratings, at $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	FR70B(R)02	FR70D(R)02	FR70G(R)02	FR70J(R)02	Unit
Repetitive peak reverse voltage	V_{RRM}		100	200	400	600	V
RMS reverse voltage	V_{RMS}		70	140	280	420	V
DC blocking voltage	V_{DC}		100	200	400	600	V
Continuous forward current	I_F	$T_C \leq 100\text{ }^{\circ}\text{C}$	70	70	70	70	A
Surge non-repetitive forward current, Half Sine Wave	I_{FSM}	$T_C = 25\text{ }^{\circ}\text{C}$, $t_p = 8.3\text{ ms}$	870	870	870	870	A
Operating temperature	T_J		-40 to 125	-40 to 125	-40 to 125	-40 to 125	$^{\circ}\text{C}$
Storage temperature	T_{stg}		-40 to 150	-40 to 150	-40 to 150	-40 to 150	$^{\circ}\text{C}$

Electrical characteristics, at $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	FR70B(R)02	FR70D(R)02	FR70G(R)02	FR70J(R)02	Unit
Diode forward voltage	V_F	$I_F = 70\text{ A}$, $T_J = 25\text{ }^{\circ}\text{C}$	1.5	1.5	1.5	1.5	V
Reverse current	I_R	$V_R = 100\text{ V}$, $T_J = 25\text{ }^{\circ}\text{C}$	25	25	25	25	μA
		$V_R = 100\text{ V}$, $T_J = 125\text{ }^{\circ}\text{C}$	15	15	15	15	mA
Recovery Time							
Maximum reverse recovery time	T_{RR}	$I_F = 0.5\text{ A}$, $I_R = 1.0\text{ A}$, $I_{RR} = 0.25\text{ A}$	200	200	200	250	nS
Thermal characteristics							
Thermal resistance, junction - case	$R_{\theta JC}$		0.8	0.8	0.8	0.8	$^{\circ}\text{C/W}$



Figure 1-Typical Forward Characteristics




Figure 2-Forward Derating Curve




Figure 3-Peak Forward Surge Current




Figure 4-Typical Reverse Characteristics

