

## ZWS75B-15/L





| Sales Region           | Worldwide                   |
|------------------------|-----------------------------|
| Series                 | ZWS-B                       |
| Status                 | Production                  |
| Feature                |                             |
| Option                 | With chassis model          |
| Option Lineup          | Please refer to here.       |
| Recommended EMC Filter | Please refer to here.       |
| Accessories            | Please refer to the catalog |



|                          | Electrical Characteristics |  |
|--------------------------|----------------------------|--|
| Input Voltage Range[AC]  | 85 to 265V                 |  |
| Input Voltage Range[DC]  | 120 to 370V                |  |
| Efficiency               | 87% Typ.                   |  |
| Rated Output Voltage[DC] | 15V                        |  |
| Output Voltage Range[DC] | 13.5 to 16.5V              |  |
| Maximum Output Current   | 5A                         |  |
| Maximum Output Power     | 75W                        |  |

|              | Cases Shape & Size |
|--------------|--------------------|
| Case'∏ shape | PC board           |
| Width(W)     | 60mm Nom.          |
| Height(H)    | 45mm Nom.          |
| Depth(D)     | 180mm Nom.         |
| Weight       | 350g Typ.          |

| er to the |
|-----------|
|           |
| f€        |

<sup>!</sup> Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website. ! All specifications are subject to change without notice.