

XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB201209-300-3A				Rev: A/1	
DIMENSION : (m/m) <div style="text-align: center; margin: 10px 0;"> </div>				A	$\varnothing 2.0 \pm 0.2$ m/m
				B	1.2 ± 0.2 m/m
				C	0.9 ± 0.2 m/m
				D	0.5 ± 0.3 m/m
				E	m/m
				F	m/m
				G	m/m
				H	m/m
				I	m/m
				J	m/m
				K	m/m
				L	m/m
				M	m/m
				N	m/m
				O	m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS	
Z	30 Ohms $\pm 25\%$	TEST FREQ.	100	MHz	<input type="radio"/> HP 34401A MULTIMETER <input type="radio"/> HP 4195 NETWORKS/SPECTRUM ANALYZER <input type="radio"/> HP 42841 BIAS CURRENT SOURCE <input type="radio"/> HP 4285A LCR METER <input type="radio"/> HP 4286A RF LCR METER <input checked="" type="radio"/> HP 4291A RF IMPEDANCE / MATERIAL ANALYZER <input type="radio"/> HP 4338A MILLION OHM METER <input type="radio"/> HP 6632A DC POWER SUPPLY <input type="radio"/> HP4284A PRECISION LCR METER
Z		TEST FREQ.		MHz	
SRF		TEST FREQ.		MHz	
Rdc	0.025 Ohms Max	TEST FREQ.		MHz	
Idc	3000mA Max	TEST FREQ.		MHz	
		TEST FREQ.			
DRAWN BY :		CHECKED BY :		APPROVED BY :	
ISAIAH MCNEIL		TONY IMBURGIA		JOE HUFF	
				9-11-01	