KM4110/KM4120

0.5mA, Low Cost, +2.7V & +5V, 75MHz Rail-to-Rail Amplifiers

Features


- 505μA supply current
- 75MHz bandwidth
- Power down to I_S = 33μA (KM4120)
- Fully specified at +2.7V and +5V supplies
- Output voltage range: 0.07V to 4.86V; V_S = +5
- Input voltage range: -0.3V to +3.8V; V_S = +5
- 50V/μs slew rate
- ±15mA linear output current
- ±30mA output short circuit current
- 12nV/√Hz input voltage noise
- Directly replaces AD8031 in single supply applications
- Small package options (SOT23-5 and SOT23-6)

Applications


- Portable/battery-powered applications
- A/D buffer
- Active filters
- Signal conditioning
- Portable test instruments

KM4110/KM4120 Packages

SOT23-5 (KM4110)



SOT23-6 (KM4120)




General Description

The KM4110 (single) and KM4120 (single with disable) are low cost, voltage feedback amplifiers. These amplifiers are designed to operate on +2.7V, +5V, or ±2.5V supplies. The input voltage range extends 300mV below the negative rail and 1.2V below the positive rail.

The KM4110 offers superior dynamic performance with a 75MHz small signal bandwidth and 50V/μs slew rate. The combination of low power, high output current drive, and rail-to-rail performance make the KM4110 well suited for battery-powered communication/ computing systems.

The combination of low cost and high performance make the KM4110 suitable for high volume applications in both consumer and industrial applications such as wireless phones, scanners, and color copiers.

Non-Inverting Freq. Response V_S = +5V



KM4110/KM4120 Electrical Characteristics (V_s = +2.7V, G = 2, R_L = 1kΩ to V_s/2, R_f = 1kΩ; unless noted)

Parameters	Conditions	TYP	Min & Max	UNITS	NOTES
Case Temperature		+25°C	+25°C		
Frequency Domain Response					
-3dB bandwidth	G = +1, V_O = 0.05V_{pp}	65		MHz	1
	G = +2, V_O < 0.2V_{pp}	30		MHz	
full power bandwidth	G = +2, V_O = 2V_{pp}	12		MHz	
gain bandwidth product		28		MHz	
Time Domain Response					
rise and fall time	0.2V step	7.5		ns	
settling time to 0.1%	1V step	60		ns	
overshoot	0.2V step,	10		%	
slew rate	2.7V step, G = -1	40		V/µs	
Distortion and Noise Response					
2nd harmonic distortion	1V_{pp}, 1MHz	67		dBc	
3rd harmonic distortion	1V_{pp}, 1MHz	72		dBc	
THD	1V_{pp}, 1MHz	65		dB	
input voltage noise	>1MHz	12		nV/√Hz	
DC Performance					
input offset voltage		0	±5	mV	2
average drift		10		µV/°C	
input bias current		1.2	±3.5	µA	2
average drift		3.5		nA/°C	
input offset current		30	350	nA	2
power supply rejection ratio	DC	66	60	dB	2
open loop gain		98	65	dB	2
quiescent current		470	600	µA	2
Disable Characteristics					
turn on time		0.54		µs	
turn off time		4.3		µs	
off isolation	5MHz, R_L = 100Ω	58		dB	
quiescent current		15		µA	
Input Characteristics					
input resistance		9		MΩ	
input capacitance		1.5		pF	
input common mode voltage range		-0.3 to 1.5		V	
common mode rejection ratio	DC, V_{cm} = 0V to V_s - 1.5	98	78	dB	2
Output Characteristics					
output voltage swing	R_L = 10kΩ to V_s/2	0.05 to 2.6		V	
	R_L = 1kΩ to V_s/2	0.05 to 2.61	0.2 to 2.35	V	2
linear output current		±15		mA	
short circuit output current		±25		mA	
power supply operating range		2.7	2.5 to 5.5	V	

Min/max ratings are based on product characterization and simulation. Individual parameters are tested as noted. Outgoing quality levels are determined from tested parameters.

NOTES:

1) For G = +1, R_f = 0.

2) 100% tested at +25°C.

Absolute Maximum Ratings

supply voltage	0 to +6V
maximum junction temperature	+175°C
storage temperature range	-65°C to +150°C
lead temperature (10 sec)	+300°C
operating temperature range (recommended)	-40°C to +85°C
input voltage range	+V_s +0.5V; -V_s -0.5V
internal power dissipation	see power derating curves

Package Thermal Resistance

Package	θ_{JA}
5 lead SOT23	256°C/W
6 lead SOT23	230°C/W

KM4110/KM4120 Electrical Characteristics (V_s = +5V, G = 2, R_L = 1kΩ to V_s/2, R_f = 1kΩ; unless noted)

PARAMETERS	CONDITIONS	TYP	MIN & MAX	UNITS	NOTES
Case Temperature		+25°C	+25°C		
Frequency Domain Response					
-3dB bandwidth	G = +1, V_O = 0.05V_{pp}	75		MHz	1
	G = +2, V_O < 0.2V_{pp}	35		MHz	
full power bandwidth	G = +2, V_O = 2V_{pp}	15		MHz	
gain bandwidth product		33		MHz	
Time Domain Response					
rise and fall time	0.2V step	6		ns	
settling time to 0.1%	2V step	60		ns	
overshoot	0.2V step,	12		%	
slew rate	5V step, G = -1	50		V/µs	
Distortion and Noise Response					
2nd harmonic distortion	2V_{pp}, 1MHz	64		dBc	
3rd harmonic distortion	2V_{pp}, 1MHz	62		dBc	
THD	2V_{pp}, 1MHz	60		dB	
input voltage noise	>1MHz	12		nV/√Hz	
DC Performance					
input offset voltage		-1	±5	mV	2
average drift		10		µV/°C	
input bias current		1.2	±3.5	µA	2
average drift		3.5		nA/°C	
input offset current		30	350	nA	2
power supply rejection ratio	DC	65	60	dB	2
open loop gain		80	65	dB	2
quiescent current		505	620	µA	2
Disable Characteristics					
turn on time		0.33		µs	
turn off time		5.5		µs	
off isolation	5MHz, R_L = 100Ω	58		dB	
quiescent current		33		µA	
Input Characteristics					
input resistance		9		MΩ	
input capacitance		1.5		pF	
input common mode voltage range		-0.3 to 3.8		V	
common mode rejection ratio	DC, V_{cm} = 0V to V_s - 1.5	92	78	dB	2
Output Characteristics					
output voltage swing	R_L = 10kΩ to V_s/2	0.08 to 4.84		V	
	R_L = 1kΩ to V_s/2	0.07 to 4.86	0.2 to 4.65	V	2
linear output current		±15		mA	
short circuit output current		±30		mA	
power supply operating range		5	2.5 to 5.5	V	

Min/max ratings are based on product characterization and simulation. Individual parameters are tested as noted. Outgoing quality levels are determined from tested parameters.


NOTES:

1) For G = +1, R_f = 0.


2) 100% tested at +25°C.

KM4110/KM4120 Performance Characteristics (V_s = +5V, G = 2, R_L = 1kΩ to V_s/2, R_f = 1kΩ; unless noted)


Non-Inverting Freq. Response V_S = +5V




Inverting Freq. Response V_S = +5V




Non-Inverting Freq. Response V_S = +2.7V




Inverting Freq. Response V_S = +2.7V




Frequency Response vs. C_L




Frequency Response vs. R_L



Large Signal Frequency Response




Frequency Response vs. Temperature




KM4110/KM4120 Performance Characteristics (V_S = +5V, G = 2, R_L = 1kΩ to V_S/2, R_f = 1kΩ; unless noted)


Open Loop Gain & Phase vs. Frequency




Input Voltage Noise




2nd & 3rd Harmonic Distortion; V_S = +5V




2nd & 3rd Harmonic Distortion; V_S = +2.7V




2nd Harmonic Distortion vs. V_O




3rd Harmonic Distortion vs. V_O



PSRR




CMRR




KM4110/KM4120 Performance Characteristics (V_S = +5V, G = 2, R_L = 1kΩ to V_S/2, R_f = 1kΩ; unless noted)


Output Current




Small Signal Pulse Response V_S = +5V




Small Signal Pulse Response V_S = +2.7V




Large Signal Pulse Response V_S = +5V



Output Swing; V_S = +2.7V; G = -1



Enable/Disable Response



General Description

The KM4110 is a single supply, general purpose, voltage-feedback amplifier fabricated on a complementary bipolar process. The KM4110 offers 75MHz unity gain bandwidth, 50V/μs slew rate, and only 505μA supply current. It features a rail-to-rail output stage and is unity gain stable.

The design utilizes a patent pending topology that provides increased slew rate performance. The common mode input range extends to 300mV below ground and to 1.2V below V_S. Exceeding these values will not cause phase reversal. However, if the input voltage exceeds the rails by more than 0.5V, the input ESD devices will begin to conduct. The output will stay at the rail during this overdrive condition.

The design uses a Darlington output stage. The output stage is short circuit protected and offers "soft" saturation protection that improves recovery time.

The typical circuit schematic is shown in Figure 1.




Figure 1: Typical Configuration

For optimum response at a gain of +2, a feedback resistor of 1kΩ is recommended. Figure 2 illustrates the KM4110 frequency response with both 1kΩ and 2kΩ feedback resistors.

Enable/Disable Function (KM4120)

The KM4120 offers an active-low disable pin that can be used to lower its supply current. Leave the pin floating to enable the part. Pull the disable pin to the negative supply (which is ground in a single supply application) to disable the output. During the disable condition, the nominal supply current will drop to below 30μA and the output will be at high impedance with about 2pF capacitance.




Figure 2: Frequency Response vs. R_f

Power Dissipation

The maximum internal power dissipation allowed is directly related to the maximum junction temperature. If the maximum junction temperature exceeds 150°C, some reliability degradation will occur. If the maximum junction temperature exceeds 175°C for an extended time, device failure may occur.

The KM4110 is short circuit protected. However, this may not guarantee that the maximum junction temperature (+150°C) is not exceeded under all conditions. Follow the maximum power derating curves shown in Figure 3 to ensure proper operation.




Figure 3: Power Derating Curves

Overdrive Recovery

For an amplifier, an overdrive condition occurs when the output and/or input ranges are exceeded. The recovery time varies based on whether the input or output is overdriven and by how much the ranges are exceeded. The KM4110 will typically recover in less than 20ns from an overdrive condition. Figure 4 shows the KM4110 in an overdriven condition.




Figure 4: Overdrive Recovery

Driving Capacitive Loads

The Frequency Response vs. C_L plot on page 4, illustrates the response of the KM4110 and KM4120. A small series resistance (R_s) at the output of the amplifier, illustrated in Figure 5, will improve stability and settling performance. R_s values in the Frequency Response vs. C_L plot were chosen to achieve maximum bandwidth with less than 1dB of peaking. For maximum flatness, use a larger R_s.




Figure 5: Typical Topology for driving a capacitive load

Layout Considerations

General layout and supply bypassing play major roles in high frequency performance. Fairchild has evaluation boards to use as a guide for high frequency layout and to aid in device testing and characterization. Follow the steps below as a basis for high frequency layout:

- Include 6.8μF and 0.01μF ceramic capacitors
- Place the 6.8μF capacitor within 0.75 inches of the power pin
- Place the 0.01μF capacitor within 0.1 inches of the power pin
- Remove the ground plane under and around the part, especially near the input and output pins to reduce parasitic capacitance
- Minimize all trace lengths to reduce series inductances

Refer to the evaluation board layouts shown in Figure 7 for more information.

Evaluation Board Information

The following evaluation boards are available to aid in the testing and layout of this device:

Eval Board	Description	Products
KEB002	Single Channel, Dual Supply 5 & 6 lead SOT23	KM4110IT5, KM4120IT6

Evaluation board schematics and layouts are shown in Figure 6 and Figure 7.

The KEB002 evaluation board is built for dual supply operation. Follow these steps to use the board in a single supply application:

1. Short -V_s to ground
2. Use C3 and C4, if the -V_s pin of the KM4110 or KM4120 is not directly connected to the ground plane.




Figure 6: Evaluation Board Schematic

KM4110/KM4120 Evaluation Board Layout




Figure 7a: KEB002 (top side)





Figure 7b: KEB002 (bottom side)

KM4110/KM4120 Package Dimensions

SOT23-5




SYMBOL	MIN	MAX
A	0.90	1.45
A1	0.00	0.15
A2	0.90	1.30
b	0.25	0.50
C	0.09	0.20
D	2.80	3.10
E	2.60	3.00
E1	1.50	1.75
L	0.35	0.55
e	0.95 ref	
e1	1.90 ref	
α	0°	10°

NOTE:

1. All dimensions are in millimeters.
2. Foot length measured reference to flat foot surface parallel to DATUM 'A' and lead surface.
3. Package outline exclusive of mold flash & metal burr.
4. Package outline inclusive of solder plating.
5. Comply to EIAJ SC74A.
6. Package ST 0003 REV A supercedes SOT-D-2005 REV C.

SOT23-6



SYMBOL	MIN	MAX
A	0.90	1.45
A1	0.00	0.15
A2	0.90	1.30
b	0.25	0.50
C	0.09	0.20
D	2.80	3.10
E	2.60	3.00
E1	1.50	1.75
L	0.35	0.55
e	0.95 ref	
e1	1.90 ref	
α	0°	10°

NOTE:

1. All dimensions are in millimeters.
2. Foot length measured reference to flat foot surface parallel to DATUM 'A' and lead surface.
3. Package outline exclusive of mold flash & metal burr.
4. Package outline inclusive of solder plating.
5. Comply to EIAJ SC74A.
6. Package ST 0004 REV A supercedes SOT-D-2006 REV C.

Ordering Information

Model	Part Number	Package	Container	Pack Qty
KM4110	KM4110IT5	SOT23-5	Partial Rail	<3000
KM4110	KM4110IT5TR3	SOT23-6	Reel	3000
KM4120	KM4120IT6	SOT23-6	Partial Rail	<3000
KM4120	KM4120IT6TR3	SOT23-6	Reel	3000

Temperature range for all parts: -40°C to +85°C

DISCLAIMER
FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICES TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY
FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2001 Fairchild Semiconductor Corporation