

塑封超快速整流二极管


反向电压 100---600V

正向电流 10A

Plastic Ultra-Fast Recover Rectifier

Reverse Voltage 100 to 600 V

Forward Current 10 A



特征 Features

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 低功耗高效率。Low Power Loss, High Efficiency
- 引线 and 管体皆符合RoHS标准。

Lead and body according with RoHS standard

机械数据 Mechanical Data

- 封装: 塑料封装 **Case: Molded Plastic**
·极性: 标记模压或印于本体 **Polarity: Symbols molded or marked on body**
·安装位置: 任意 **Mounting Position: Any**
·安装扭矩: 推荐值 0.3牛*米 **Mounting torque: Recommend 0.3 N*m**

极限值和温度特性 TA = 25℃ 除非另有规定。

TA = 25℃ 除非另有规定。

Maximum Ratings & Thermal Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	MUR1010	MUR1020	MUR1040	MUR1060	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	100	200	400	600	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	70	140	280	420	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	100	200	400	600	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}	10				A
峰值正向浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}	100				A
典型热阻 Typical thermal resistance	R _{θJC}	3.0		2.0		℃/W
工作结温和存储温度 Operating junction and storage temperature range	T _J , T _{STG}	-55---+150				℃

电特性 TA = 25℃ 除非另有规定。

TA = 25°C 除非另有规定。

Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

		符号 Symbols	MUR1010	MUR1020	MUR1040	MUR1060	单位 Unit
最大正向电压 Maximum forward voltage	$I_F = 10A$	V_F	1.00		1.30	1.50	V
最大反向电流 Maximum reverse current	$T_A = 25^\circ C$ $T_A = 125^\circ C$	I_R	10 250				μA
最大反向恢复时间 MAX. Reverse Recovery Time	$I_F = 0.5A$ $I_R = 1.0A$ $I_{REC} = 0.25A$	t_{rr}	35		50		nS

特性曲线 Characteristic Curves

