


**Data sheet | Item number: 221-942**

Jumper; for conductor entry; 2-way; insulated; dark gray

[www.wago.com/221-942](http://www.wago.com/221-942)



Color: █

## Data

### Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

**Ratings per IEC/EN**

Nominal voltage (III/3)	400 V
Rated current	41 A

**Physical data**

Jumper assignment	1-2
-------------------	-----

**Material data**

Note (material data)	Information on material data can be found here
Color	dark gray
Insulation material	Polyamide (PA66)
Weight of insulation material	0.28 g
Weight	2.7 g

**Environmental requirements**

Continuous operating temperature	-60 ... +105 °C
----------------------------------	-----------------

**Commercial data**

ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	5 Pieces
Packaging type	bag
Country of origin VKOrg Germany	CN
GTIN	4055144067965
Customs tariff number VKOrg Germany	85366990990

**Downloads****Documentation****Bid Text**

221-942 doc - Datei	docx 28.2 kB	Download
221-942 X81 - Datei	xml 3.0 kB	Download

Subject to changes. Please also observe the further product documentation!

### Additional Information

Technical Section	pdf	Download
Technical explanations	2.2 MB	

---

### Environmental Product Compliance


#### Compliance Search

Environmental Product Compliance 221-942	URL	Download
Jumper; for conductor entry; 2-way; insulated; dark gray		

---

### Installation Notes

#### Commoning



Extending the N and PE (ground) distribution via jumper

#### Commoning



Insert the jumper without a locking function into open clamping units.

#### Commoning

---


Subject to changes. Please also observe the further product documentation!



Without a locking function:

The jumper without a locking function is plugged into the splicing connectors.

### Commoning



Remove the jumper from open clamping units.

Subject to changes. Please also observe the further product documentation!