

PIN Assignment

P1		P2
1	WHITE	1
2	GREY	2
3	YELLOW	3
4	PINK	4
5	ORANGE	5
6	RED	6
7	BROWN	7
8	GREEN	8
10	BLUE	10
11	PURPLE	11
12	LIGHT GREEN	12
13	LIGHT BLUE	13
14	BLACK	14
15	WHITE/BLACK	15
Shell	DRAIN	Shell

Material:

1. CABLE: NON-UL 28AWG(7/0.127)TC*14C INS:PVC+DRAIN WIRE(26AWG 7/0.16)+AL-FOIL/MYLAR
   PVC JACKET COLOR:BEIGE, OD:6.0±0.2mm
2. CONNECTOR:
   P1&P2:HD15P MALE GOLD FLASH CONTACT,
   NICKEL PLATED SHELL(THE 9TH PIN UNLOAD)
3. HOOD:MOLDED TYPE PVC 45P COLOR:BEIGE.
4. ELECTRICAL TEST:
   <1>100% OPEN SHORT & MIS WIRE TEST.
   <2>CONTACT RESISTANCE 3 Ohms MAX.
   <3>INSULATION RESISTANCE 20M Ohms MIN.
5. PACKING:SEE P-0039 REV.C PACKING DRAWING+EAN CODE
   PACKING TYPE: DB VP4
   (HANKING SIZE MUST BE SMALLER THAN PACKING)

RoHS Complaint

Scale	1:1						Name
TOLERANCE					Drawn	11.16.11	Chappell
X.X	±0.40				Approved		
X.XX	±0.25						
X.XXX	±0.15						
Angle	±3°						
			Modification	Date	Name		

ASSMANN WSW components

Item No. **AK376-R**

Title VGA Moniter Extension Cable, HD D-Sub 15 pin Male <=> Male, 3 Meters

Drawing No. **rev00**

Replace | Sheet