




Price** : 1,548.00 USD



Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 20 VA Class 1 25 VA
Line Rated Current	1500 A

Complementary

Current transformer type	Tropicalised for busbar
Current transformer ratio	1500/5
[Ith] conventional free air thermal current	60 kA
Dynamic withstand current	2.5 Ith
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
[Ui] rated insulation voltage	3 kV
Mounting mode	Insulated locking screw
Mounting support	Busbar
Width	Inner 2.17 in (55 mm) Outside 5.31 in (135 mm)
Height	Outside 5.08 in (129 mm) Inner 4.06 in (103 mm)
Depth	Frame 1.97 in (50 mm) Total 3.35 in (85 mm)
Net weight	1.53 lb(US) (0.692 kg)
[Uimp] rated impulse withstand voltage	3 kV

Electrical insulation class	Class B
Opening of bars	102 x 54
Sealing	With

Environment

Standards	IEC 61869-2 VDE 0414
Product certifications	CE
IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	-13...122 °F (-25...50 °C)

Ordering and shipping details

Category	01290 - MASTERPACT ACCESSORIES
Discount Schedule	DE2F
GTIN	03606480618963
Returnability	No
Country of origin	TN

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.