

Applications

- Time delay in turning off the auxiliary winding of single-phase AC motors (e.g. refrigerator compressors)

Features

- Thermistor disk encapsulated in heat-resistant, flame-retardant plastic case with connections for compressor power supplies and tab connectors
- Metallization: CrNi (sputtered) + Ag (screen-printed)
- Excellent long-term reliability
- VDE approval (license number 87406 E), except J 524
- UL approval for J 501 and J 506 acc. to demands of UL 1434 and UL 873 (file number E161049)


Options

- Other dimensions and ratings on request
- Other terminal options on request

Delivery mode

- Cardboard box

Dimensional drawing



A : one tab connector version
A + B : two tab connectors version
A + B + C : three tab connectors version

TPT0658-B-E

Motor Starting	B5919*, B595**
Metallized Disks in EPCOS Housing	J 19*, J 5**

General technical data

Switching cycles	N	> 100000	
Operating temperature range ($V = 0$)	T_{op}	+ 5/+ 80	°C
($V = V_{max}$)	T_{op}	+ 5/+ 80	°C

Electrical specifications and ordering codes

Type	I_{max}	V_{max}	T_{Ref}	T_{surf}	$t_S^{1)}$	V_{BD}	$R_N \pm \Delta R_N$ ($V_{PTC} \leq 2,5 \text{ V}$)	I_r	Ordering code
	A	V	°C	°C	s	V	Ω	mA	
$V_N = 230 \text{ V}_{rms}$									
J 502	4	400	120	180	0,55	> 750	$47 \pm 30 \%$	8	B59502J0120A*20
J 501	6	355	135	190	0,45	> 700	$33 \pm 20 \%$	8	B59501J0135A*20
J 524	7	300	135	190	0,55	> 600	$22 \pm 20 \%$	10	B59524J0135A*20
J 544	8	320	120	180	0,35	> 650	$20 \pm 20 \%$	12	B59544J0120A*20
J 192	8	325	120	180	0,35	> 650	$25 \pm 15/-20 \%$	10	B59192J0120A*20
J 196	8	350	120	180	0,50	> 700	$15 \pm 30 \%$	10	B59196J0120A*20
J 197	9	350	120	180	0,30	> 700	$33 \pm 30 \%$	8	B59197J0120A*20
$V_N = 120 \text{ V}_{rms}$									
J 508	10	180	135	190	0,55	> 360	$4,7 \pm 20 \%$	17	B59508J0135A*20
J 506	12	180	120	180	0,45	> 360	$4,7 \pm 20 \%$	16	B59506J0120A*20

Replace * by 1 $\triangleq$ one tab connector
 * by 2 $\triangleq$ two tab connectors
 * by 3 $\triangleq$ three tab connectors

1) Measured at $V = V_{max}$ and $I = 0,8 \cdot I_{max}$

Motor Starting	B5919*, B595**
Metallized Disks in EPCOS Housing	J 19*, J 5**

Reliability data

Test ¹⁾	Standard	Test conditions	$ \Delta R_{25}/R_{25} $
Switching test at room temperature	IEC 60738-1	$V_{\max}$; R_S Room temperature Number of cycles: 10000	< 25 %
Life test at $V_{\max}/T_{\text{op}}$	IEC 60738-1	Storage at $V_{\max}/T_{\text{op}}$ for t : 1000 h	< 25 %
Damp heat	IEC 60068-2-3	Storage at 40 °C Relative humidity: 93 % Duration: 56 days	< 20 %
Rapid change of temperature in air	IEC 60068-2-14, Test N_a	– 25 °C, 125 °C Number of cycles: 5 t : 30 min	< 20 %
Vibration	IEC 60068-2-6, Test F_C	$f = 10\text{--}55\text{--}10$ Hz $h = 0,75$ mm (respectively 10 g) t : 3 · 2 h	< 20 %
Bump	IEC 60068-2-27	Pulse shape: half-sine a : = 40 g Pulse duration: 6 ms; 6 · 4000 pulses	< 20 %
Climatic sequence	IEC 60068-2-30	Dry heat: $T = 125$ °C, t : 16 h Damp heat first cycle Cold: $T = -25$ °C, t : 2 h Damp heat 5 cycles	< 25 %

1) All tests with PTC disk mounted in EPCOS housing

Herausgegeben von EPCOS AG

Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.