

May, 2015

3M™ Scotch® Clean Removal Multipack Tape 694

Product Description

Scotch® Clean Removal Multipack Tape 694 is an adhesive tape recommended for multipack/product bundling purposes. It secures bundles yet does not damage primary packaging when removed. This is a packaging alternative to plastic bags, shrink wrap, chipboard, paperboard, and trays. It can increase the customers' productivity, reduce secondary packaging material by weight, and improve packaging design. This tape is available in a clear and a custom printed version and can be utilized for product promotion and branding. It has a conformable backing and a low adhesion acrylic adhesive.



Product Features

- Clean removal and repositionable without damage to primary packaging.
- Application to wide variety of surfaces including printed cardboard, printed chipboard and paperboard, plastic bags, bottles, and pouches.
- Biaxially oriented film backing provides good resistance to humidity, ensuring better performance during aging.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Clear and Printed		
Total Tape Thickness	0.48 mm	1.9 mil	ASTM D3652
Backing Thickness	0.4 mm	1.6 mil	ASTM D3652
Backing	Biaxially oriented polypropylene		
Adhesive	Acrylic Pressure Sensitive		

Typical Performance Characteristics

Property	Values		Method	Backing	Notes
180° Peel Adhesion	0.4 N/cm	4 oz/in	ASTM D3330	2 mil Aluminum Foil	12 in/min (300 mm/min) 72 hr dwell on Stainless Steel
Tensile Strength	52.5 N/cm	30 lb/in	ASTM D3759		
Elongation at Break	130 %		ASTM D3759		

Available Sizes

Property	Values	
Note	Subject to Minimum Order Requirements	
Standard Roll Length	100, 1500 m	109, 1640 yd
Available Width	36, 48, 72, 96, 144 mm	

Handling/Application Information

Application Techniques

Application equipment including hand held manual dispensers, semi-automatic and fully automatic equipment for grouping packages are available. Application of Scotch® Multipack Tape 694 is most easily accomplished at room temperature 72°F (23°C). Very low or high temperatures cause hardening or softening of the adhesive respectively, making application more difficult. Once applied, Scotch® Multipack Tape 694 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended. To obtain best performance, use this product within 18 months from date of manufacture.

Trademarks

Scotch is a registered trademark of 3M.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all- 3m-products/~/Scotch-Clean-Removal-Multipack- Tape-694?N=5002385+3292136718&rt=rud

Table continued on next page

3M™ Scotch® Clean Removal Multipack Tape 694

References (continued)

Property	Values
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=694

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Scotch® Clean Removal Multipack Tape 694

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



