

Rating: 10A 125V AC
6A 250V AC

Function: ON-OFF

Contact Resistance: 50mΩ Max

Dielectric Strength: AC1500V 1 minute

Electrical life: 10,000 cycles

Operating Pressure: 600gf ±300gf

MATERIAL:

Body: Nylon66, UL rated: 94V-2 min


Actuator: Nylon66, UL rated: 94V-2 min

Terminal: Brass, silver plated

Operating Temperature: -20°C ~ 80°C

Safety Approval:

CUT-OUT



	X	Y
0.75~1.25	19.2-0.1	13.0+0.1
1.25~2.00	19.4-0.1	13.0+0.1
2.00~3.00	19.8-0.1	13.0+0.1



公差 TOLEANCES .X± 0.3 .XX± 0.15 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VERSION	A0	比例尺 SCALE	日期 DATE	2018.06.04	品名 TITLE	图号 DRAWING NO
------------	----	-----------	---------	------------	----------	---------------

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	孙成	MR-2-210-C5N-BB	MR-2-210-C5N-BB_A0
--------	-------------------------	---------	---------	----------------	---------------	-------------	----	-----------------	--------------------