Product data sheet
Characteristics

BDL36045LW
PowerPact B Circuit Breaker, 45A, 3P, 14kA@600Y/347V (UL), Control Wire

Product availability : Non-Stock - Not normally stocked in distribution facility

Price** : 1,201.00 USD



Main

Range	PowerPact
Product name	PowerPact B
Device short name	BD 045
Product or component type	Circuit breaker
Device application	Distribution
Accessory / separate part type	Control wire

Complementary

Number of Poles	3P
Control type	Toggle
Breaking capacity code	D
Breaking capacity	25 kA 208Y/120 V AC 50/60 Hz UL 489 25 kA 240 V AC 50/60 Hz UL 489 18 kA 480/277 V AC 50/60 Hz UL 489 18 kA 480 V AC 50/60 Hz UL 489 14 kA 600Y/347 V AC 50/60 Hz UL 489 10 kA 250 V DC UL 489
[Ue] rated operational voltage	525 V AC 50/60 Hz UL 489
[Ics] rated service breaking capacity	25 kA 220...240 V AC 50/60 Hz IEC 60947-2 14 kA 500...525 V AC 50/60 Hz IEC 60947-2 18 kA 380...415 V AC 50/60 Hz IEC 60947-2 18 kA 440 V AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2
[Ui] rated insulation voltage	800 V IEC 60947-2
Trip unit technology	Thermal-magnetic
Suitability for isolation	Yes IEC 60947-2
Utilisation category	Category A
Mechanical durability	IEC 947-1 Annex K ed 5.2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Electrical durability	10000 cycles IEC 947-1 Annex K ed 5.2 440 V In
Local signalling	Presence of auxiliary contacts flag green)
Mounting mode	Clip-on 35 x 15 mm symmetrical DIN rail) By screws plate)
Electrical connection	Everlink lug line Everlink lug load
AWG gauge	AWG 6...AWG 2/0 fine stranded copper AWG 14...AWG 3/0 rigid or stranded copper
Tightening torque	44.25 lbf.in (5 N.m) 0.00…0.02 in² (2.5…16 mm²) AWG 14...AWG 4) 79.66 lbf.in (9 N.m) 0.04…0.15 in² (25…95 mm²) AWG 3...AWG 3/0)
Number of slots	auxiliary switch OF plug-in) voltage release MN or MX plug-in) alarm switch SD plug-in)
Color	Gray RAL 7016)
Quantity per set	Set of 1
Continuous current rating	80 %

Environment

Quality labels	CE
Standards	UL 489 NMX J-266 EN/IEC 60947-2 EN/IEC 60947-5-1 GB 14048.2 CSA C22.2 No 5 NEMA AB1
Product certifications	UL IEC CCC EAC CSA NOM
IP degree of protection	Front cover IP40 IEC 60529
IK degree of protection	IK07 IEC 62262
Pollution degree	3 IEC 60947-1
Operating altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating

Ordering and shipping details

Category	01130 - BD UNIT MOUNT BREAKER/SWITCH
Discount Schedule	DE2
Package weight(Lbs)	2.92 lb(US) (1.32 kg)
Returnability	No
Country of origin	US