SPLICER TERMINAL BLOCKS

- Quick mounting and wiring
- IP20 Finger Safe
- DIN Rail or Panel Mount
- No caps to open or remove
- Material
  Housing: Polyamide
  Metal Body: Aluminum

38064	38057	38059
		

Part Number:	38064		38057		38059	
Approvals	UL File E98082	IEC	UL File E98082	IEC	UL File E98082	IEC
Current Rating	175A	175A	400A	400A	800A	800A
Voltage Rating	600V AC	690V AC	600V AC	690V AC	600V AC	690V AC
No. of Inputs	1	1	1	1	2	2
Wire Range	14-1AWG	2.5mm²-50mm²	6AWG-400MCM	16mm²-185mm²	3AWG-600MCM	25-300mm²
Torque	106.2lb.-in.	12Nm	221lb.-in.	25Nm	310lb.-in.	35Nm
Screw Type	Hex 5		Hex 10		Hex 10	
No. of Outputs	1	1	1	1	2	2
Wire Range	14-1AWG	2.5mm²-50mm²	6AWG-400MCM	16mm²-185mm²	3AWG-600MCM	25-300mm²
Torque	106.2lb.-in.	12Nm	221lb.-in.	25Nm	310lb.-in.	35Nm
Screw Type	Hex 5		Hex 10		HEx 10	

Dimensions:

