

# Series 800 Mighty Mouse Metal Protective Covers with UN Mating Thread 667-184 and 667-185 Ordering Information



Protective covers fit Series 800 plug and receptacle connectors. Aluminum or stainless steel. Fluorosilicone rubber gasket protects connector from contamination and water ingress. Attach to panel or cable with a variety of lanyards and fittings. Lanyard styles include braided nylon rope, stainless steel wire or sash chain. Stainless steel wire available with flexible, rugged polyurethane coating or Teflon™ sleeve for high temperature requirements.

| How To Order                          |  |
|---------------------------------------|--|
| <b>Sample Part Number</b>             | <b>667-184</b> -M -G 9 04 -6 X   |
| <b>Series (See Table I)</b>           | 667-184 = Plug Cover<br>667-185 = Receptacle Cover   |
| <b>Shell Material and Finish</b>      | C = Aluminum / Black Anodize (Non-Conductive) RoHS Compliant<br>M = Aluminum / Electroless Nickel RoHS Compliant<br>MT = Aluminum / Nickel-PTFE RoHS Compliant<br>NF = Aluminum / Cadmium with Olive Drab Chromate<br>ZNU = Aluminum / Zinc-Nickel with Black Chromate<br>Z1 = Stainless Steel / Passivated RoHS Compliant                         |
| <b>Attachment Type</b>                | -D = Bead Chain, CRES, Passivate<br>-F = Wire Rope, Nylon Jacket<br>-G = Nylon Rope<br>-H = SST Wire Rope, Teflon® Jacket<br>-N = No Attachment<br>-R = Wire Rope, PVC Jacket<br>-S = SST Sash Chain<br>-SK = Nylon Rope With Slip Knot<br>-T = SST Wire Rope, No Jacket<br>-U = SST Wire Rope, Polyurethane Jacket<br><br>"SST" = Stainless Steel |
| <b>Shell Size</b>                     | 5, 6, 7, 8, 9, 10, 12  |
| <b>Attachment Code (See Table II)</b> | Small Ring = 01, 02, 04, 06<br>Large Ring = 14 thru 33<br>Split Ring = 50 thru 68  |
| <b>Attachment Length (Inches)</b>     | Omit for attachment Type N (No Attachment)<br>Example: "-6" equals six inch length   |
| <b>Alternate Polarization</b>         | X, Y, Z; Omit for Normal   |

| Table I: Shell Style         |                                    |
|------------------------------|------------------------------------|
|                              |                                    |
| <b>667-184</b><br>Plug Cover | <b>667-185</b><br>Receptacle Cover |

| Table II: Attachment Code  |                                |
|--|--------------------------------|
| Omit for attachment types <b>N</b> (No Attachment) and <b>SK</b> (Slip Knot) |                                |
|  | <b>00</b> - No Eyelet          |
|  | <b>01</b> - .125 (3.2) I.D.    |
|  | <b>02</b> - .145 (3.6) I.D.    |
|  | <b>04</b> - .182 (4.6) I.D.    |
|  | <b>06</b> - .197 (5.0) I.D.    |
|  | <b>32</b> - .265 (6.73) I.D.   |
|  | <b>29</b> - .315 (8.00) I.D.   |
|  | <b>14</b> - .385 (9.78) I.D.   |
|  | <b>15</b> - .445 (11.30) I.D.  |
|  | <b>33</b> - .510 (12.95) I.D.  |
|  | <b>16</b> - .570 (14.48) I.D.  |
|  | <b>17</b> - .635 (16.13) I.D.  |
|  | <b>18</b> - .695 (17.65) I.D.  |
| <b>27</b> - .766 (19.46) I.D.  |                                |
|  | <b>50</b> - .432 (11.0) I.D.   |
|  | <b>52</b> - .492 (12.5) I.D.   |
|  | <b>54</b> - .648 (16.5) I.D.   |
|  | <b>56</b> - .757 (19.2) I.D.   |
|  | <b>58</b> - .898 (22.8) I.D.   |
|  | <b>60</b> - 1.023 (26.01) I.D. |
| <b>64</b> - 1.137 (28.9) I.D.  |                                |
| <b>68</b> - 1.357 (34.5) I.D.  |                                |

Dimensions in Inches (millimeters) are subject to change without notice.