STP4403


P Channel Enhancement Mode MOSFET

- 10.0A

DESCRIPTION

STP4403 is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application, such as cellular phone and notebook computer power management and other battery powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

PIN CONFIGURATION
SOP-8




FEATURE

- -20V/-10.0A, $R_{DS(ON)}$ = 20mΩ @V_{GS} = -4.5V
- -20V/-8.6A, $R_{DS(ON)}$ = 25mΩ @V_{GS} = -2.5V
- -20V/-7.6A, $R_{DS(ON)}$ = 35mΩ @V_{GS} = -1.8V
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOP-8 package design

PART MARKING
SOP-8



Y:Year Code
A:Process Code



STANSON TECHNOLOGY
120 Bentley Square, Mountain View, Ca 94040 USA
www.stansontech.com

Copyright © 2007, Stanson Corp.

STANSON

STP4403

Lead-free

P Channel Enhancement Mode MOSFET

- 10.0A

ABSOULTE MAXIMUM RATINGS (Ta = 25℃ Unless otherwise noted)

Parameter		Symbol	Typical	Unit
Drain-Source Voltage		VDSS	-20	V
Gate-Source Voltage		VGSS	±12	V
Continuous Drain Current (TJ=150℃)	TA=25℃ TA=70℃	ID	-10.0 -8.0	A
Pulsed Drain Current		IDM	-30	A
Continuous Source Current (Diode Conduction)		IS	-2.3	A
Power Dissipation	TA=25℃ TA=70℃	PD	2.8 1.8	W
Operation Junction Temperature		TJ	-55/150	℃
Storgae Temperature Range		TSTG	-55/150	℃
Thermal Resistance-Junction to Ambient		RθJA	70	℃/W

STANSON TECHNOLOGY
120 Bentley Square, Mountain View, Ca 94040 USA
www.stansontech.com

Copyright © 2007, Stanson Corp.


ELECTRICAL CHARACTERISTICS (Ta = 25℃ Unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V,ID=-250uA	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},ID=-250uA	-0.35		-0.9	V
Gate Leakage Current	I_{GSS}	V_{DS}=0V,V_{GS}=±12V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-16V,V_{GS}=0V			-1	uA
		V_{DS}=-20V,V_{GS}=0V T_J=55℃			-10	
On-State Drain Current	$I_{D(on)}$	V_{DS}=-5V,V_{GS}=-4.5V	-20			A
Drain-source On-Resistance	$R_{DS(on)}$	V_{GS}=-4.5V,I_D=-10A V_{GS}=-2.5V,I_D=-8.6A V_{GS}=-1.8V,I_D=-7.6A		16 20 28	20 25 35	mΩ
Forward Transconductance	gfs	V_{DS}=-5.0V,I_D=-10A		36		S
Diode Forward Voltage	V_{SD}	I_S=-2.5A,V_{GS}=0V		-0.8	-1.2	V
Dynamic						
Total Gate Charge	Q_g	V_{DS}=-10V,V_{GS}=-5V I_D=-10.0A		30	45	nC
Gate-Source Charge	Q_{gs}			4.5		
Gate-Drain Charge	Q_{gd}			8.0		
Input Capacitance	C_{iss}	V_{DS} ==-10V,VGS=0V f=1MHz		2670		pF
Output Capacitance	C_{oss}			520		
Reverse TransferCapacitance	C_{rss}			480		
Turn-On Time	$t_{d(on)}$	V_{DD}=-10V,R_L=15Ω I_D=-1A,V_{GEN}=-4.5V R_G=6Ω		25	40	nS
	tr			45	70	
Turn-Off Time	$t_{d(off)}$			145	240	
	tf			70	115	


STANSON TECHNOLOGY
120 Bentley Square, Mountain View, Ca 94040 USA
www.stansontech.com

Copyright © 2007, Stanson Corp.


TYPICAL CHARACTERICTICS




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance



Gate Charge




On-Resistance vs. Junction Temperature


STANSON TECHNOLOGY
120 Bentley Square, Mountain View, Ca 94040 USA
www.stansontech.com

Copyright © 2007, Stanson Corp.


TYPICAL CHARACTERICTICS




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage



Single Pulse Power, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot

STANSON TECHNOLOGY
120 Bentley Square, Mountain View, Ca 94040 USA
www.stansontech.com

Copyright © 2007, Stanson Corp.

PACKAGE OUTLINE SOP-8P



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	——	0.25	0.004	——	0.010
A2	——	1.45	——	——	0.057	——
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	——	1.27	——	——	0.050	——
L	0.38	0.71	1.27	0.015	0.028	0.050
② y	——	——	0.076	——	——	0.003
θ	0°	——	8°	0°	——	8°

STANSON TECHNOLOGY
120 Bentley Square, Mountain View, Ca 94040 USA
www.stansontech.com

Copyright © 2007, Stanson Corp.