
MB2505 THRU MB2510

SINGLE PHASE 25 AMP BRIDGE RECTIFIERS

GW



FEATURES

* Superior thermal design
* 300 amperes surge capability
* Mounting: Hole thru for #8 screw
* 1/4" universal faston terminal


VOLTAGE RANGE

50 to 1000 Volts

CURRENT

25.0 Amperes

MB-25



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25˚C ambient temperature unless otherwies specified.
Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

TYPE NUMBER	MB2505	MB251	MB252	MB254	MB256	MB258	MB2510	UNITS
Maximum Recurrent Peak Reverse Voltage	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current .375"(9.5mm) Lead Length at Tc=55˚C	25							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	300							A
Maximum Forward Voltage Drop per Bridge Element at 12.5AD.C.	1.1							V
Maximum DC Reverse Current Ta=25˚C	10							μA
at Rated DC Blocking Voltage Ta=100˚C	500							μA
Operating Temperature Range, T_J	-65 — +125							˚C
Storage Temperature Range, T_{STG}	-65 — +150							˚C

RATING AND CHARACTERISTIC CURVES (MB2505 THRU MB2510)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS

