Housing - HC-HPR-B24-BFH-EMR-BK - 1411055

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON B24 panel mounting base, HPR series, for screw locking, for increased environmental and EMC requirements

Your advantages

- Vibration and shock: IEC 61373/EN 50155, category 1, class 1B

Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 921688
GTIN	4046356921688

Technical data

Dimensions

Height	20 mm
Width	58 mm
Length	192 mm
Length of the assembly cutout	108 mm
Width of the assembly cutout	35 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
	IP68 (0.5 bar / 24 h)
	IP69K (ISO 20653:2013-02)
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	For contact inserts HC-B24, BB46, BBB64, D64, DD108, M
Size	B24

Housing - HC-HPR-B24-BFH-EMR-BK - 1411055

Technical data

General


Housing type	Panel mounting base
Color	black
Locking type	with screw locking
Torque	4 Nm (Locking screw)
Screw connection	none
Protective cover	no
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, black
Seal material	NBR
Material lock	Stainless steel
Material of locking screw	Stainless steel

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing



Dimensional drawing

Mounting cutout

Approvals

Approvals

Approvals

GL / EAC

Ex Approvals

Approval details

Housing - HC-HPR-B24-BFH-EMR-BK - 1411055

Approvals

GL	GL	http://exchange.dnv.com/tari/	6196614 HH

EAC	EAC	RU C-DE.AI30.B.01102

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com