

NND15-1515



<b>Sales Region</b>	Worldwide
<b>Series</b>	NND
<b>Status</b>	Production
<b>Feature</b>	
<b>Option</b>	
<b>Option Lineup</b>	
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 115V 170 to 230V
Input Voltage Range[DC]	
Efficiency	45% Typ.
Rated Output Voltage[DC]	<u>+15V</u> <u>-15V</u>
Output Voltage Range[DC]	<u>+13.5 to +16.5V</u> <u>-13.5 to -16.5V</u>
Minimum Output Current	
Maximum Output Current	<u>0.6A</u> <u>0.6A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	18W
Total Maximum Peak Power	

### Cases Shape & Size

Case'□' shape	Unit
Width(W)	60mm Nom.
Height(H)	113.5mm Nom.
Depth(D)	150mm Nom.
Weight	1750g Typ.

### Other

Operating Temp. Range	-20 to 71°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	

