

KR Electronics, Inc.

General Description


KR 2997 is a 70 MHz bandpass filter. The minimum 3 dB bandwidth is 4 MHz. Other center frequencies and bandwidths available. Please consult the factory.

Features

- 70 MHz Center Frequency
- 4 MHz min 3 dB Bandwidth
- SMA Connectors
- 50 Ω Source and Load

Typical Performance

Overall Response (10 dB/div)




KR Electronics, Inc.
91 Avenel Street
Avenel, NJ 07001


Web www.krfilters.com
Email sales@krfilters.com
Phone (732) 636-1900
Fax (732) 636-1982

Typical Performance

Passband Amplitude & Group Delay (1 dB/div & 20 nsec/div)



Overall Stopband to 1 GHz (10 dB/div)



KR Electronics, Inc.
91 Avenel Street
Avenel, NJ 07001


Web www.krfilters.com
Email sales@krfilters.com
Phone (732) 636-1900
Fax (732) 636-1982

KR Electronics 2997

Specifications

Parameter	Specification	Typical / Notes
Filter type	Bandpass	
Center Frequency	70 MHz	
Insertion Loss	5.5 dB max	3.5 typical
Minimum 3 dB Bandwidth	4 MHz	
20 dB Bandwidth	7.3 MHz typical	
40 dB Bandwidth	11.4 MHz typical	
60 dB Bandwidth	17.9 MHz typical	
Source and Load	50 Ω	

Physical Dimensions



Notes:

1. Dimensions in inches
2. Rectangular case

KR Electronics, Inc.
91 Avenel Street
Avenel, NJ 07001

Web www.krfilters.com
Email sales@krfilters.com
Phone (732) 636-1900
Fax (732) 636-1982