# Panel feed-through terminal block - HDFK 25 GNYE - 0707769

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The illustration shows version HDFK 25 in gray

Panel feed-through terminal block, Connection method: Screw connection, Screw connection, Cross section: 6 mm² - 35 mm², AWG 10 - 2, Width: 15.1 mm, Color: green-yellow

## Key Commercial Data

| | |
|---|---|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| GTIN | 4 017918 004217 |
| Weight per Piece (excluding packing) | 67.39 g |
| Custom tariff number | 85369010 |
| Country of origin | Greece |

## Technical data

### General

| | |
|---|---|
| Number of levels | 1 |
| Number of connections | 2 |
| Color | green-yellow |
| Insulating material | PA |
| Flammability rating according to UL 94 | V0 |
| Rated surge voltage | 6 kV |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulating material group | I |
| Nominal current $I_N$ | 125 A |
| Nominal voltage $U_N$ | 500 V |
| Number of positions | 1 |

### Dimensions

# Panel feed-through terminal block - HDFK 25 GNYE - 0707769

## Technical data

### Dimensions

| | |
|---|---|
| Width | 15.1 mm |

### Connection data

| | |
|---|---|
| Note | Terminal sleeve |
| Connection side | Level 1 ext. 1 |
| Connection method | Screw connection |
| Note | Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area. |
| Conductor cross section solid min. | 6 mm² |
| Conductor cross section solid max. | 35 mm² |
| Conductor cross section flexible min. | 10 mm² |
| Conductor cross section flexible max. | 25 mm² |
| Conductor cross section AWG min. | 10 |
| Conductor cross section AWG max. | 2 |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 4 mm² |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 25 mm² |
| Conductor cross section flexible, with ferrule with plastic sleeve min. | 4 mm² |
| Conductor cross section flexible, with ferrule with plastic sleeve max. | 25 mm² |
| 2 conductors with same cross section, solid min. | 2.5 mm² |
| 2 conductors with same cross section, solid max. | 10 mm² |
| 2 conductors with same cross section, stranded min. | 4 mm² |
| 2 conductors with same cross section, stranded max. | 10 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 2.5 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 10 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 2.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 10 mm² |
| Stripping length | 19 mm |
| Internal cylindrical gage | B8 |
| Screw thread | M5 |
| Tightening torque, min | 4 Nm |
| Tightening torque max | 4.5 Nm |
| Connection side | Level 1 int. 1 |
| Connection method | Screw connection |
| Conductor cross section solid min. | 6 mm² |
| Conductor cross section solid max. | 35 mm² |

# Panel feed-through terminal block - HDFK 25 GNYE - 0707769

## Technical data

### Connection data

| | |
|---|---|
| Conductor cross section flexible min. | 10 mm² |
| Conductor cross section flexible max. | 25 mm² |
| Conductor cross section AWG min. | 10 |
| Conductor cross section AWG max. | 2 |
| Internal cylindrical gage | B8 |

### Standards and Regulations

| | |
|---|---|
| Connection in acc. with standard | CSA |
| | IEC / EN |
| Flammability rating according to UL 94 | V0 |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141134 |
| eCl@ss 5.1 | 27141134 |
| eCl@ss 6.0 | 27141134 |
| eCl@ss 7.0 | 27141134 |
| eCl@ss 8.0 | 27141134 |

### ETIM

| | |
|---|---|
| ETIM 2.0 | EC001283 |
| ETIM 3.0 | EC001283 |
| ETIM 4.0 | EC001283 |
| ETIM 5.0 | EC001283 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

## Approvals

### Approvals

# Panel feed-through terminal block - HDFK 25 GNYE - 0707769

## Approvals

Approvals

CSA / UL Recognized / EAC

Ex Approvals

Approvals submitted

## Approval details

CSA

| | | B | C |
|---|---|---|---|
| mm²/AWG/kcmil | 8-4 | 8-4 | 8-4 |
| Nominal current IN | 100 A | 100 A | 100 A |
| Nominal voltage UN | 600 V | 600 V | 600 V |

UL Recognized

| | B | C |
|---|---|---|
| mm²/AWG/kcmil | 8-2 | 8-2 |
| Nominal current IN | 115 A | 115 A |
| Nominal voltage UN | 600 V | 600 V |

EAC

Phoenix Contact 2015 © - all rights reserved
http://www.phoenixcontact.com