



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 121.5 MHz SMD 7.0x5.0 mm (BW=0.05 MHz)

TST Part No.: TA1952A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ David Chang 

Approved by: _____ Bob Chau 

Date: _____ 2016/01/12

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com

Web: www.taisaw.com

SAW Filter 121.5 MHz

MODEL NO.: TA1952A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 15 dBm
2. DC Voltage : 10 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -45°C to +90°C

RoHS Compliant
Lead free
Lead-free soldering


Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Typ.	Max.
Center frequency F_c	MHz	-	121.5	-
Insertion Loss (121.475~121.525 MHz) IL	dB	-	1.4	2.5
Bandwidth @ -1dB	MHz	0.05	1.75	-
Amplitude Ripple (121.475~121.525 MHz)	dB	-	0.1	1.2
Attenuation (Reference level from 0 dB)				
101.5 ~ 113.5 MHz	dB	40	52	-
113.5 ~ 116.5 MHz	dB	20	31	-
116.5 ~ 118.5 MHz	dB	15	35	-
118.5 ~ 119.3 MHz	dB	5	58	-
123.7 ~ 124.5 MHz	dB	5	15	-
124.5 ~ 126.5 MHz	dB	12	16	-
126.5 ~ 129.5 MHz	dB	16	22	-
129.5 ~ 141.5 MHz	dB	36	41	-
Temperature coefficient of frequency	ppm/k	-	-32	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer



D. OUTLINE DRAWING:



Pin configuration

- #9 Input
- #4 Output
- #10 Input ground
- #5 Output ground
- #1,2,3,6,7,8 To be grounded
- △ : Year code
- : Date code (Follow the table from planner each year)


Product Year Code

Year	2009 2013	2010 2014	2011 2015	2012 2016
Product Code	A	a	<u>A</u>	<u>a</u>




Date Code Table:

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

E. PCB Footprint:




F. Frequency Characteristics:




G. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

